

TB DAVIES

Always within reach



LOFT LADDERS





NEXT DAY DELIVERY



1 YEAR WARRANTY



MAX LOAD 150 KG



REGULAR USAGE

LuxFold

A quality timber loft ladder that uses traditional dovetail woodworking techniques

The TB Davies LuxFold timber loft ladders are produced using Renewable Energy and the finest PEFC sustainably sourced timbers. The Nordic Spruce treads connect to the stiles using craftsman's dovetail joints to provide a strong, robust ladder for regular climbing. Double counterbalanced trap door allows smooth fingertip control incorporating an integrated twin action lock, to ensure the very tightest fitting. The extra thick 87mm trapdoor delivers an industry leading U-Value of just 0.59W/m²K (the lower the figure, the better the insulation) and features a clean white finish to enhance your décor. The ladder is mounted on the hatch to use minimum of storage space. The ladder is fully assembled so do not require any additional pre-installation work.

- Industry leading insulation value of 0.59W/m²K
- Double lock for maximum draught exclusion and security
- Finger-tip dual action counterbalance operating system
- Includes handrail for added safety
- Slip resistant feet for extra security
- Fully assembled – simply fit into loft aperture
- Requires no headroom or storage space in the loft
- 87mm extra -thick insulated white trapdoor
- 27mm thick frame with continuous seal around trap door reduces heat loss
- Manufactured using 100% renewable energy
- PEFC sustainably sourced timber
- EN14975



*Product Information

LUXFOLD TIMBER LOFT LADDER							
SKU	Treads x Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance (mm)	Going (mm)	Weight (kg)
1530-010	4 x 3	1200 x 700	1190 x 690	2800	550	1200	33.5







NEXT DAY DELIVERY



1 YEAR WARRANTY



MAX LOAD 150 KG



REGULAR USAGE

EnviroFold

Ecological and sustainable quality

This TB Davies EnviroFold Loft Ladder is partially assembled for quick and easy installation into your loft. The well insulated trapdoor is finished in white with rubber draught excluders to prevent heat loss. Suitable for ceiling heights up to heights up to 2.8m the innovative design takes up no space in the attic.

- Insulation value of 1.11W/m²K
- Fits between standard UK loft joists
- Includes handrail for added safety
- Slip resistant feet for extra security
- Final assembly for quick installation
- Requires no headroom or storage space in the loft
- 33mm thick insulated white trapdoor
- 18mm thick frame with continuous seal around trap door reduces heat loss
- Manufactured using 100% renewable energy
- PEFC sustainably sourced timber
- EN14975



*Product Information



ENVIROFOLD TIMBER LOFT LADDER

SKU	Treads x Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance (mm)	Going (mm)	Weight (kg)
1530-005	4 x 3	1200 x 550	1190 x 540	2800	550	1200	26.5

TB Davies | For orders and enquiries call: 029 2132 0000





NEXT DAY
DELIVERY



1 YEAR
WARRANTY



MAX LOAD
150 KG



REGULAR
USAGE

EuroFold

Practical and affordable loft access with an insulated trapdoor

The TB Davies EuroFold 3 Section Loft Ladder requires no headroom or storage space in the loft. Precision manufactured in Europe's Clean Tech Valley using Renewable Energy and PEFC sustainably sourced timber. The Nordic Spruce construction uses traditional dovetail techniques that provide a strong, robust ladder for regular climbing. The continuous draught seal provides a tight air-seal to reduce draughts.

- Insulation value of 1.11W/m²K
- Fits between standard UK loft joists
- Requires no headroom or storage space in the loft
- Some assembly required before installation
- 33mm thick insulated white trapdoor
- Spring counter balancing system for easy operation
- 18mm thick frame, together with continuous seal keeps cool draughts out
- Slip resistant dovetail treads
- Manufactured using 100% renewable energy
- PEFC sustainably sourced timber
- EN14975



*Product Information



EUROFOLD TIMBER LOFT LADDER							
SKU	Treads x Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance (mm)	Going (mm)	Weight (kg)
1530-000	4 x 3	1200 x 550	1190 x 540	2800	550	1200	26.0

TB Davies | For orders and enquiries call: 029 2132 0000





NEXT DAY DELIVERY



1 YEAR WARRANTY



MAX LOAD 150 KG



REGULAR USAGE

FireFold

Built to withstand fire up to 30 minutes

Built to the same standard and specification as the LuxFold, but designed to withstand fire for up to 30 minutes (EL₂30) fire rating. Suitable for properties with more than 3 floors or passive houses that require a fire rated loft ladder. Fitted with a continuous seal to keep draughts out. The ladder is fully assembled, just requires final installation tweaks.

- Fire rated to 30 minutes - EN1363, EN1634, B3860
- Insulation value of 0.67W/m²K
- Requires no headroom or storage space in the loft
- Includes handrail for added safety
- 60mm thick insulated white trapdoor
- Spring counter balancing system for easy operation
- 27mm thick frame, together with continuous seal keeps cool draughts out
- Slip resistant dovetail treads
- Manufactured using 100% renewable energy
- PEFC sustainably sourced timber
- EN14975



*Product Information



FIREFOLD TIMBER LOFT LADDER							
SKU	Treads x Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance (mm)	Going (mm)	Weight (kg)
1530-040	4 x 3	1200 x 600	1190 x 590	2750	550	1200	27.5



NEXT DAY DELIVERY



1 YEAR WARRANTY



MAX LOAD 150 KG



REGULAR USAGE

MiniFold

Making even the smallest loft spaces available

From the same stable of Loft Ladders as its siblings, the LuxFold, EnviroFold and EuroFold. This is an all in-one hatch with metal concertina loft ladder stair.

- Insulation value of 1.11W/m²K
- Requires no headroom or storage space in the loft
- 33mm thick insulated white trapdoor
- Spring counter balancing system for easy operation
- 18mm thick MDF frame with continuous seal around trap door reduces heat loss
- 360mm wide, metal platform treads
- Manufactured using 100% renewable energy
- EN14975



*Wide deep metal treads for comfort whilst climbing



*Product Information



MINIFOLD LOFT LADDER

SKU	Treads x Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance (mm)	Going (mm)	Weight (kg)
1530-050	11 x 1	900 x 700	890 x 690	3000	750	1200	40.5

For orders and enquiries call: **029 2132 0000** | TB Davies



DELIVERY
28 days



1 YEAR
WARRANTY



MAX LOAD
150 KG



REGULAR
USAGE

Electric Loft Ladder

Ultra elegance electric loft ladder for ease

Press the remote control and watch the loft hatch open to reveal the concertina ladder drop down in a smooth, continuous movement enabling you to get in and out of the loft space with comfort and ease. Built with the same frame as the MiniFold, but with the added luxury of an electric motor. The Electric Loft Ladder also benefits from being fire rated to 30 minutes.

- Fire rated to 30 minutes - EN1363, EN1634, B3860
- Insulation value of 1.3W/m²K
- Electric motor driven loft ladder makes it easier to use your loft space
- Supplied with a remote control unit
- Requires no headroom or storage space in the loft
- 65mm thick insulated white trapdoor
- Supplied in a powder coated metal frame with continuous seal that reduces heat loss
- 360mm wide, metal platform treads
- Manufactured using 100% renewable energy
- EN14975



*Product Information



ELECTRIC LOFT LADDER							
SKU	Treads x Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance (mm)	Going (mm)	Weight (kg)
1530-060	11 x 1	1200 x 700	1190 x 690	2900	580	1530	90.5

Comparison Table

Let us help you decide which loft ladder suits your needs



	EuroFold	EnviroFold	FireFold	LuxFold	MiniFold	Electric
Tested to U-Value	1.11W/m2k	1.11W/m2k	0.66W/m2k	0.59W/m2k	1.11W/m2k	1.3W/m2k
Hatch Thickness	33mm	33mm	60mm	87mm	33mm	65mm
Material - Frame	Spruce	Spruce	Spruce	Spruce	MDF	Metal + MDF
Material - Stile	Nordic Spruce	Nordic Spruce	Nordic Spruce	Nordic Spruce	Metal	Metal
Material - Tread	Nordic Spruce	Nordic Spruce	Nordic Spruce	Nordic Spruce	Metal	Metal
Handrail	-	Yes(x1)	Yes(x1)	Yes(x1)	-	-
Assembly	Final Assembly Required	Final Assembly Required	Final Assembly Required	Fully Assembled	Assembly Required	Assembly Required
Lock Mechanism	Simple	Simple	Simple	2-Part Metal Lock System	-	-
Tread Joint	Dove-Tailed	Dove-Tailed	Dove-Tailed	Dove-Tailed	-	-
Feet on Ladder	-	Yes	Yes	Yes	Yes	Yes
Loft Ladder Pole	Yes (Timber)	Yes (Timber)	Yes (Timber)	Yes (Metal)	Yes (Timber)	-
Fire Rated (EN 1634)	-	-	Yes	-	-	-
Operation	Manual	Manual	Manual	Manual	Manual	AUTOMATIC (Remote)
Standard EN 14975	Yes	Yes	Yes	Yes	Yes	Yes

Accessories

Timber Loft Balustrade Kit

3-sided balustrade kit suitable for all loft openings. This complete kit includes everything you need to assemble a handrail system around your loft opening. The 71 x 126cm handrail is easy to cut to size and fit. We supply the balustrade ready to paint or varnish to match your home decor. The handrail secures the loft opening along both sides and across the back and stops you or your family members using the loft from falling.



LOFT LADDERS

TB Davies Cardiff Ltd,
Lewis Road, Cardiff,
CF24 5EB
T: 029 2132 0000
F: 029 2070 2386
E: sales@tbdavies.co.uk
www.tbdavies.co.uk

Registered in England No. 534073
VAT Registration No. GB134144207

