







	EUROFOLD	ENVIROFOLD	FIREFOLD	LUXFOLD	MINIFOLD	ELECTRIC
						
TESTED TO U-VALUE (LOWER IS BETTER)	1.11W/m ² K	1.11W/m ² K	0.667W/m ² K	0.59W/m ² K	1.11W/m ² K	1.3W/m ² K
HATCH THICKNESS	33mm	33mm	60mm	87mm	33mm	65mm
MATERIAL - FRAME	Plywood	Plywood	Spruce	Spruce	MDF	Metal + MDF
MATERIAL - STILE	Nordic Spruce	Nordic Spruce	Nordic Spruce	Nordic Spruce	Metal	Metal
MATERIAL - TREAD	Nordic Spruce	Nordic Spruce	Nordic Spruce	Nordic Spruce	Metal	Metal
HANDRAIL	–	Yes (x1)	Yes (x1)	Yes (x1)	–	–
ASSEMBLY	Final Assembly Required	Final Assembly Required	Final Assembly Required	Fully Assembled	Assembly Required	Assembly Required
LOCK MECHANISM	Simple	Simple	2-Part Metal Lock System	2-Part Metal Lock System	–	–
TREAD JOINT	Dove-Tailed	Dove-Tailed	Dove-Tailed	Dove-Tailed	–	–
LOFT LADDER POLE	Yes (Timber)	Yes (Timber)	Yes (Timber)	Yes (Metal)	Yes (Metal)	–
OPERATION	Manual	Manual	Manual	Manual	Manual	Electric (Remote)
FIRE RATED (EN1634) 30-MINUTES	–	–	Yes	–	–	–
SAFETY STANDARD	EN14975	EN14975	EN14975	EN14975	EN14975	EN14975