

Tubesca EN131 Pro MP Platform Step Ladder



[Representative image of product]

Features

- Protected with an impermeable, hygienic and abrasive resistant anodised armour
- Fitted with twin handrails for maximum safety
- Large 85mm deep steps provide increased climbing support
- Extra-strong 280 x 250mm top platform tread, die cast for additional strength
- Spacious integrated plastic tool tray
- Featuring tough spun-rung, Duraclimb technology for intensive use
- Oversized feet ensure maximum ground contact and grip

Product Dimensions

SKU	Treads ²	Approx. Working Height ¹ (mm)	Platform Height (mm)	Closed Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1206-003	3	2260	660	1480	480	790	5.4
1206-004	4	2480	880	1730	520	950	6.4
1206-005	5	2700	1100	1970	570	1100	8.5
1206-006	6	2920	1320	2210	610	1250	9.7
1206-007	7	3140	1540	2460	660	1410	11.3
1206-008	8	3360	1760	2700	700	1560	12.6
1206-009	9	3580	1980	2940	740	1710	14.4
1206-010	10	3800	2200	3180	790	1870	17.2
1206-012	12	4240	2640	3670	880	2180	20.6

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

² Treads includes top platform step/top cap tool tray tread

Specifications

- Warranty: 5-year
- Standard: EN131 Professional
- Material: Anodised Aluminium
- Commodity Code: 76169990
- Recommended Usage: Intensive

Common Dimensions

- Tread Depth: 90mm
- Distance Between Treads: 250mm
- Storage Depth: 120mm
- Top Platform Tread (LxW): 280 x 250mm
- Handrail Height: 650mm

Availability & Delivery

Special order. Please call for details.
 (See exceptions, if applicable, overleaf)

Tubesca EN131 Pro MP Platform Step Ladder

Product Description

The MP Pro Platform Step is precision engineered for performance and is protected with an impermeable, hygienic and abrasive resistant anodised armour that has low electricity and heat transfer properties. The large 90mm deep treads are secured using Duraclimb spun-rung technology to provide the strongest possible mechanical connection for intensive use. Ideal for use in high-tech manufacturing environments including pharmaceutical, aerospace, telecommunications and technology.

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1206-003	3178740001681	1480	480	120	0.085	5.4
1206-004	3178740001421	1730	520	120	0.108	6.4
1206-005	3178740001063	1970	570	120	0.135	8.5
1206-006	3178740004583	2210	610	120	0.162	9.7
1206-007	3178740002015	2460	660	120	0.195	11.3
1206-008	3178740000400	2700	700	120	0.227	12.6
1206-009	5060169488748	2940	740	120	0.261	14.4
1206-010	3178740000882	3180	790	120	0.301	17.2
1206-012	3178740002466	3670	880	120	0.388	20.6

Packaging Material: Polywrap

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.