

Sherpamatic Podium



Common Dimensions

Tread Depth (mm)	80
Platform Tread (W x D) (mm)	600 x 420

Product Dimensions

PRODUCT SKU	TREAD COUNT	APPROX. WORKING HEIGHT* (M)	PLATFORM HEIGHT (M)	CLOSED HEIGHT (M)	WIDTH (MM)	OPEN DEPTH (MM)	WEIGHT (NETT KG)
1274-003	3	2.3	0.7	2.1	800	1,200	16.9
1274-004	4	2.6	1.0	2.3	660	1,390	20.1
1274-005	5	2.8	1.2	2.6	660	1,570	21.8
1274-006	6	3.0	1.4	2.8	660	1,750	23.3
1274-007	7	3.3	1.7	3.1	660	1,930	25.2

- * Working height is calculated as 1,600mm plus the height of the platform or last climbing tread, whichever is appropriate.
- Tread count includes top platform step.



Technical Description

The large solid podium has a full height guardrail, which is accessed through a gate which completely protects the operator from falls. The unit folds easily for transportation and is fitted with telescopic stabilisers for maximum stability. Also available in non-conductive fibreglass which is ideal for use around electricity.

- » Rung to rung telescopic height adjustment
- » Fully enclosed guardrail provides 360-degree protection
- » Large anti-slip work platform 600 x 420mm
- » Fitted with 100mm toe boards
- » Twin stabilisers to provide maximum stability
- » Compact and easy to transport and store
- » Large diameter wheels for ease of movement around site

Standards & Classification

- » Max Load 150kg
- » PIRL 93 353 / PIR 93 352

Warranty

- » 5 Years

Commodity Code

- » 76169990

Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (MM)	SHIPPING WIDTH (MM)	SHIPPING DEPTH (MM)	SHIPPING VOLUME (M ³)	SHIPPING WEIGHT (GROSS KG)	BARCODE
1274-003	2,070	800	320	0.5299	16.9	3178740098612
1274-004	2,300	660	320	0.4858	20.1	3178740098629
1274-005	2,550	660	320	0.5386	21.8	3178740098636
1274-006	2,800	660	320	0.5914	23.3	3178740098643
1274-007	3,050	660	320	0.6442	25.2	3178740098650