

Sherpamatic Podium (Fibreglass)



Common Dimensions

Tread Depth (mm)	80
Platform Tread (W x D) (mm)	600 x 420

Product Dimensions

PRODUCT SKU	TREAD COUNT	APPROX. WORKING HEIGHT* (M)	PLATFORM HEIGHT (M)	CLOSED HEIGHT (M)	WIDTH (MM)	OPEN DEPTH (MM)	WEIGHT (NETT KG)
1274-023	3	2.3	0.7	2.1	660	1,230	18.7
1274-024	4	2.5	0.9	2.3	660	1,400	19.4
1274-025	5	2.8	1.2	2.6	660	1,600	20.7

- * Working height is calculated as 1,600mm plus the height of the platform or last climbing tread, whichever is appropriate.
- Tread count includes top platform step.



Technical Description

The large solid podium has a full height guardrail, which is accessed through a gate which completely protects the operator from falls. The unit folds easily for transportation and is fitted with telescopic stabilisers for maximum stability. Also available in non-conductive fibreglass which is ideal for use around electricity.

- » Non-conductive fibreglass stiles to 30,000 volts (EN61478)
- » Rung to rung telescopic height adjustment
- » Fully enclosed guardrail provides 360-degree protection
- » Large anti-slip work platform 600 x 420mm
- » Fitted with 100mm toe boards
- » Twin stabilisers to provide maximum stability
- » Compact and easy to transport and store
- » Large diameter wheels for ease of movement around site

Standards & Classification

- » Max Load 150kg
- » PIRL 93 353 / PIR 93 352

Warranty

- » 5 Years

Commodity Code

- » 70199000

Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (M)	SHIPPING WIDTH (MM)	SHIPPING DEPTH (MM)	SHIPPING VOLUME (M ³)	SHIPPING WEIGHT (GROSS KG)	BARCODE
1274-023	2,070	660	320	0.4372	18.7	3178740161934
1274-024	2,300	660	320	0.4858	19.4	3178740161941
1274-025	2,550	660	320	0.5386	20.7	3178740161958