



Industrial PAS 250 / Podium Steps



Product Dimensions

PRODUCT SKU	TREAD COUNT	APPROX. WORKING HEIGHT* (M)	MIN. PLATFORM HEIGHT (M)	MAX. PLATFORM HEIGHT (M)	OPEN HEIGHT (M)	CLOSED HEIGHT (M)	WIDTH (MM)	WIDTH STABILISERS (M)	OPEN DEPTH (M)	WEIGHT (KG)
1274-070	-	2.0	0.4	0.4	1.4	1.4	675	-	1.4	19.0
1274-071	-	2.1	0.5	0.5	1.5	1.5	675	-	1.4	22.0
1274-072	2	2.4	0.5	0.8	1.8	1.8	675	1.9	1.4	31.0
1274-073	3	2.6	0.8	1.0	2.1	2.1	675	1.9	1.4	33.0
1274-074	4	2.9	1.0	1.3	2.3	2.3	675	1.9	1.4	34.0
1274-075	5	3.1	1.3	1.5	2.6	2.6	950	2.2	1.4	40.0
1274-076	6	3.4	1.5	1.8	2.8	2.8	950	2.2	1.4	43.0
1274-077	7	3.6	1.8	2.0	3.1	3.1	950	2.2	1.4	46.0

Optional Extras

PRODUCT SKU	DESCRIPTION
1274-079	Base Plates for Podiums



Technical Description

Manufactured using 50mm diameter corrosion resistant aluminium scaffold tube for use in tough construction environments. The fully welded frames fold using durable cast aluminium components and locking castors for easy transportation.

- Tough anti-slip aluminium platform
- Impact and wear resistant 125mm nythane locking castors
- Fitted with mini stabilisers for maximum stability
- Folds flat for ease of handling and transportation

Standards & Classification

- » Max Load 150kg
- » PAS250

Warranty

- » 5 Years

Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (MM)	SHIPPING WIDTH (MM)	SHIPPING DEPTH (MM)	SHIPPING VOLUME (M ³)	SHIPPING WEIGHT (GROSS KG)	BARCODE
1274-070	1,400	250	1,400	0.4900	19.0	5060356912506
1274-071	1,500	250	1,400	0.5250	22.0	5060356912513
1274-072	1,800	250	1,400	0.6300	31.0	5060356912520
1274-073	2,100	250	1,400	0.7350	33.0	5060356912537
1274-074	2,300	250	1,400	0.8050	34.0	5060356912544
1274-075	2,600	250	1,400	0.9100	40.0	5060356912551
1274-076	2,800	250	1,400	0.9800	43.0	5060356912568
1274-077	3,100	250	1,400	1.0850	46.0	5060356912575