



# Adjustable Tripod Ladder (HPM)



## Product Dimensions

PRODUCT SKU	TREAD COUNT	LADDER HEIGHT (M)	LADDER WIDTH (M)	OPEN DEPTH (M)	FRONT LEGS LENGTH + MAX. ADJUSTMENT (MM)	BACK LEG LENGTH + MAX. ADJUSTMENT (MM)	WEIGHT (NETT KG)
1274-500	6	2,2	1,2	1,3	1,500 + 645	1,465 + 840	7.1
1274-501	8	2,8	1,5	1,6	2,100 + 645	1,765 + 1,140	8.7
1274-502	10	3,4	1,8	2,0	2,700 + 645	2,365 + 1,140	11.2
1274-503	12	4,0	1,8	2,3	3,300 + 645	2,965 + 1,140	12.7
1274-407	Protective rubber boot - set of 3						



## Technical Description

This ladder will perform all of the same tasks as the standard Tripod ladder, but due to all 3 legs being adjustable, it opens up all kinds of further opportunities, making it the most universal Tripod ladder in our range.

The rear 3rd leg is telescopic and adjustable in 150mm stages. The two front legs can be independently adjusted in 50mm steps with spring loaded locking pins. This allows the ladder to be used on steps and stairs and at virtually any angle on quite steep slopes, yet providing a stable, safe, comfortable work position.

Using this ladder you can really access places otherwise inaccessible such as beside ditches, combinations of walls, steps, slopes and banks.

- » Manufactured from welded aluminium alloy extrusions
- » Lightweight yet strong ladder to work from
- » Will not wobble on uneven ground

## Standards & Classification

- » Maximum Static Vertical Load 100kg

## Warranty

- » 1 Year

## Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (M)	SHIPPING WIDTH (M)	SHIPPING DEPTH (MM)	SHIPPING VOLUME (M <sup>3</sup> )	SHIPPING WEIGHT (GROSS KG)	BARCODE
1274-500	2,2	1,2	200	0.5376	7.1	5060169485136
1274-501	2,8	1,5	200	0.8373	8.7	5060169485143
1274-502	3,4	1,8	200	1.1844	11.2	5060169485150
1274-503	4,0	1,8	200	1.3946	12.7	5060169485167
1274-407						5060356911561