

Industrial Combination Ladder



Configurations possible with this ladder

Fig. 1




Fig. 2





Fig. 3



Product Dimensions

Rung Pitch (mm)	270
Rung Depth (mm)	30
Stabiliser Width (mm)	830 - 1280
Ladder Width Lower (mm)	500
Ladder Width Middle (mm)	450
Ladder Width Upper (mm)	390

EXTENSION LADDER FIG1

PRODUCT SKU	NOMINAL LENGTH (M)	APPROX. WORKING HEIGHT (EXT. LADDER) (M)	LAST CLIMBING HEIGHT EXTENSION LADDER ^B (M)	RUNG COUNT	CLOSED LENGTH (M)	EXTENDED LENGTH ^A (M)	STORAGE DEPTH (M)	STABILISER WIDTH (MM)	STILE WIDTH X DEPTH (M)	WEIGHT KG
1300-051	2.0	4.5	2.9	5+6+6	2.0	4.2	0.2	830 -1280	65 x 25	17.0
1300-053	2.6	6.0	4.4	7+8+8	2.6	5.7	0.2	830 -1280	65 x 25	22.0
1300-054	2.9	6.6	5.0	8+9+9	2.9	6.3	0.2	830 -1280	80 x 25	29.0
1300-056	3.5	8.4	6.8	10+11+11	3.5	8.1	0.2	830 -1280	80 x 25	35.0

STEP LADDER FIG2

EXTENDED STEP LADDER FIG3

PRODUCT SKU	OPEN STEP DEPTH (M)	A-FRAME OPEN STEP HEIGHT ^C (M)	APPROX. WORKING HEIGHT (M)	LAST CLIMBING HEIGHT ^D (M)	EXT. A-FRAME OPEN STEP HEIGHT ^E (M)	APPROX. WORKING HEIGHT (M)	LAST CLIMBING HEIGHT ^F (M)
1300-051	1.3	1.9	2.4	0.8	2.8	3.5	1.9
1300-053	1.6	2.5	3.0	1.4	4.0	4.1	2.5
1300-054	1.8	2.8	3.2	1.6	4.5	4.4	2.8
1300-056	2.3	3.4	3.8	2.2	5.6	5.0	3.4



Technical Description

Designed to be stable on uneven surfaces and offer the ultimate in durability and flexibility. Developed for use in the most demanding environments, our industrial grade combination ladders provide you a triple ladder, an A-frame stepladder, an extended stepladder, a stairwell ladder combined with a levelling safety base in one robust product. Also available with the same features in non-conductive fibreglass for use around electricity.

- » Telescopic stabiliser for use on uneven ground
- » Large box section stiles with twist-proof rung connections
- » Use as an extension, A-frame or stairwell ladder
- » Aluminium locking stays for additional rigidity
- » Reduce fatigue with deep, comfortable rungs that are horizontal when climbing
- » Strong nylon coated guides for smooth operation
- » Integrated wall wheels to assist placement

Standards & Classification

- » Max Load 150kg
- » EN131

Warranty

- » 5 Years

Commodity Code

- » 76169990

Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (MM)	SHIPPING WIDTH (MM)	SHIPPING DEPTH (MM)	SHIPPING VOLUME (M ³)	SHIPPING WEIGHT (GROSS KG)	BARCODE
1300-051	2,040	830	204	0.3454	16.0	5060356910922
1300-053	2,640	830	204	0.4470	20.5	5060356910939
1300-054	2,940	830	204	0.4978	25.0	5060356910946
1300-056	3,540	830	234	0.6875	29.5	5060356910953

Spare Parts

PRODUCT SKU	DESCRIPTION
1300-060J	Set of 2 Plug in Feet (25 x 65mm)
1300-060K	Set of 2 Plug in Feet (25 x 80mm)