

TB Davies FireFold Loft Ladder



[Representative image of product]

Features

- Complies to EN 14975, EN 1368 & EN 1634 (Fire rated to 30 minutes)
- Tested U-Value of 0.67W/m2K for greater insulation and reduced heat loss
- 60mm deep insulated white trapdoor with metal locking key and double lock for improved draught exclusion and security
- 27mm thick frame features continuous seal that keeps cool drafts out
- Supplied with slip-resistant feet and handrail for extra security
- Fully assembled, simply fit into loft aperture
- Requires no headroom or storage space in the loft
- Manufactured using PEFC sustainably sourced timber & 100% renewable energy

Product Dimensions

SKU	Treads /Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance Length (mm)	Going (mm)
1530-040	4 x 3	1200 x 600	1190 x 590	2750	550	1200

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1530-040	5060356917570	1200	600	310	0.223	28.0

Packaging Material: Carton, Plastic

Specifications

- Warranty: 1-year
- Max Load: 150kg
- Standard: EN14975
- Material: Timber
- Commodity Code: 44189990
- Country of Origin: AT
- Recommended Usage: Regular

Frame Dimensions

- Distance Between Treads: 235mm
- Tread Width: 345mm
- Tread Depth: 80mm
- Tested U-Value: **0.667W/m²K**
- Insulated Hatch Thickness: 60mm
- Frame/Stile/Tread: Spruce/Nordic Spruce/Nordic Spruce

Availability & Delivery

Stock item. Delivery next day.
(See exceptions, if applicable, overleaf)