

TB Davies Electric Loft Ladder



[Representative image of product]

Features

- Fire rated to 30 minutes - EN1363, EN1634, B3860
- Tested U-Value of 1.3W/m²K for improved insulation and reduced heat loss
- 65mm deep insulated white trapdoor with metal locking key and double lock for improved draught exclusion and security
- 18mm frame fitted with continuous draft seal keeps drafts from coming through into house
- Supplied with a remote control fob
- Optional external box suitable for roof top access
- Manufactured using 100% renewable energy

Product Dimensions

SKU	Treads /Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance Length (mm)	Going (mm)
1530-060	11 x 1	1200 x 700	1190 x 690	2900	580	1530

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1530-060	5060356917624	1280	780	550	0.549	91.0

Packaging Material: Carton, Plastic

Specifications

- Warranty: 1-year
- Standard: EN14975
- Material: Mild Steel
- Commodity Code: 73089098
- Country of Origin: AT
- Recommended Usage: Regular

Frame Dimensions

- Distance Between Treads: 235mm
- Tread Width: 360mm
- Tread Depth: 110mm
- Tested U-Value: **1.3W/m²K**
- Insulated Hatch Thickness: 65mm
- Frame/Stile/Tread: Metal/MDF/Metal/Metal

Availability & Delivery

Special order. Please call for details.
 (See exceptions, if applicable, overleaf)