



British Standard Stepmobile



KM 608967
BS EN 131-7



Product Dimensions

PRODUCT SKU	TREAD COUNT	APPROX. WORKING HEIGHT* (M)	PLATFORM HEIGHT (M)	PLATFORM WIDTH (M)	PLATFORM DEPTH (M)	OVERALL HEIGHT (M)	OVERALL WIDTH (M)	OVERALL DEPTH (M)	WEIGHT (NETT KG)
2010-062	2	2.1	0.5	0.4	0.4	1.5	0.6	0.7	14.0
2010-063	3	2.4	0.8	0.4	0.4	1.7	0.8	0.9	16.0
2010-064	4	2.6	1.0	0.4	0.4	2.0	1.0	1.1	19.0
2010-065	5	2.9	1.3	0.4	0.4	2.2	1.2	1.2	22.0

»*Working height is calculated as 1,600mm plus the height of the platform or last climbing tread, whichever is appropriate.

»Tread count includes top platform step



Technical Description

Manufactured to the demanding requirements of British Standards EN131-7 with a flared base for maximum stability. Strong sprung castors lock and hold in place when weight is applied with long double handrails and a guard railed top tread provide extra assurance for users.

- » Flared base for added stability
- » Spring loaded swivel castors retract when weight is applied
- » Dome covers have high grip rubber wrap-around bumpers
- » Large 180mm ribbed rubber covered treads
- » Large 406 x 406mm platform
- » Continuous hand and guardrail for safety
- » Robust tubular steel construction
- » Hard wearing powder coated finish in a choice of colour
- » ***Not suitable for outdoor use*** - see galvanised option below

Standards & Classification

- » Max Load 150kg
- » EN131-7

Warranty

- » 1 Year

Commodity Code

- » 73269030

Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (HEIGHT) (MM)	SHIPPING WIDTH (MM)	SHIPPING DEPTH (MM)	SHIPPING VOLUME (M ³)	SHIPPING WEIGHT (GROSS KG)	BARCODE
2010-062	1,500	600	700	0.6300	14.0	
2010-063	1,700	800	900	1.2240	16.0	
2010-064	2,000	1,000	1,100	2.2000	19.0	
2010-065	2,200	1,200	1,200	3.1680	22.0	

Additional Options

- » Product can be supplied as galvanised

Please call our sales team to discuss these options*