

# TB Davies Extra Heavy Duty Mobile In Red With Ribbed Rubber Tread



[Representative image of product]

## Product Description

Suitable for the most demanding projects and applications, constructed from box section steel on a splayed base to provide much greater stability and strength. Over tested to 200kg. The treads are available in either expamet or ribbed rubber depending on your requirements. Kite-marked to the demanding EN131-7 British Standard. The Extra Heavy-Duty step is available with a wide range of options, including gates, chains and hinged bars.

## Features

- Extra wide 490 x 180mm deep treads for comfort and safety
- Large 500 x 560mm platform with intermediate guardrails and toe boards
- Fully welded steel box-section construction
- Additional bracing for more frequent use applications
- Choice of ribbed rubber or expamet treads
- Locking device and anti-ascent bar
- Easy one-user manoeuvrability on 200mm diameter heavy-duty wheels and 100mm swivel castors
- EN131-7

## Product Dimensions

SKU	Treads	Platform Height	Approx. Working Height <sup>1</sup> (mm)	Height (mm)	Width (mm)	Depth (mm)	Nett Weight (kg)
2025-003	3	690	2290	1690	955	780	56.0
2025-004	4		1600	1920	1120	850	64.0
2025-005	5	1150	2750	2150	1290	910	74.0
2025-006	6	1380	2980	2380	1425	960	93.0
2025-007	7	1610	3210	2610	1610	1010	102.0
2025-008	8	1840	3440	2840	1790	1060	112.0
2025-009	9	2070	3670	3070	1955	1140	122.0
2025-010	10	2300	3900	3300	2130	1220	136.0
2025-011	11	2530	4130	3530	2290	1270	145.0
2025-012	12	2760	4360	3760	2400	1270	157.0
2025-013	13	2990	4590	3990	2560	1370	168.0
2025-014	14	3220	4820	4220	2730	1540	180.0
2025-015	15	3450	5050	4450	2890	1565	192.0

<sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

## Specifications

- Warranty: 1-year
- Max Load: 150kg
- Standard: BS EN131-7
- Material: Mild Steel
- Commodity Code: 73269030
- Country of Origin: GB
- Recommended Usage: Intensive

## Common Dimensions

- Rung Depth: 0mm
- Distance Between Rungs: 0mm
- Handrail Height: 0mm

## Availability & Delivery

(See exceptions, if applicable, overleaf)

Note that 10 tread and above are supplied in 2 sections, which require bolting together before first use.

## Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m <sup>3</sup> )	Gross Weight (kg)
2025-003	5060356918140	1690	955	780	1.259	56.0
2025-004	5060356918157	1920	1120	850	1.828	64.0
2025-005	5060356918164	2150	1290	910	2.524	74.0
2025-006	5060356918171	2380	1425	960	3.256	93.0
2025-007	5060356918188	2610	1610	1010	4.244	102.0
2025-008	5060356918195	2840	1790	1060	5.389	112.0
2025-009	5060356918201	3070	1955	1140	6.842	122.0
2025-010	5060356918218	3300	2130	1220	8.575	136.0
2025-011	5060356918225	3530	2290	1270	10.266	145.0
2025-012	5060356918232	3760	2400	1270	11.46	157.0
2025-013	5060356918249	3990	2560	1370	13.994	168.0
2025-014	5060356918256	4220	2730	1540	17.742	180.0
2025-015	5060356918263	4450	2890	1565	20.127	192.0

**Packaging Material:** No Packaging

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.  
This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

TB Davies (Cardiff) Ltd, Lewis Road, Cardiff, CF24 5EB. t:+44(0)29 2132 0000 www.tbdavies.co.uk Registered in England No. 00534073, VAT Reg. No. GB134144207  
Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.