

3T Double Width Vertical Ladder 2.0 x 1.35m Scaffold Tower



[Representative image of product]

Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 250kg
- Standard: BS EN 1004:2004
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: GB
- Recommended Usage: Intensive

Common Dimensions

- Platform Length: 2000mm
- Platform Width: 1350mm
- Distance Between Rungs: 232mm

Product Description

Ideal for use in industrial environments, this is a heavy-duty scaffold tower that is built using the 3T method or Through The Trap. Top-level quality components include locking castors, threaded levelling legs, locking brace hooks. Vertical Ladder design, with a built-in ladder section and rungs, spaced 232mm apart. Spare parts are available to replace damaged components or if you need to build additional platform heights. Manufactured in the UK, this range of scaffold towers is also available in double-width and a variety of platform sizes, from 2.0m, 2.5m and 3.0m lengths.

Features

- Fully compliant using the 3T or Through The Trap build method
- 50mm scaffold tube construction with a heavy-duty spigot for maximum strength and crimped abuse-resistant joints
- Toe-board and guardrails for additional security
- Large trapdoor for easy access to top platform
- Quick assembly - designed for the professional user
- Rating - Platform 250kg / Structure 750kg
- Also available as a Single Width tower

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.
This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

3T Double Width Vertical Ladder 2.0 x 1.35m Scaffold Tower

Product Dimensions

SKU	Platform Height ² (mm)	Overall Height (mm)	Approx. Working Height ¹ (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3001-030	1410	2660	3010	n/a x n/a	86.0
3001-031	1880	3130	3480	n/a x n/a	102.0
3001-032	2340	3590	3940	n/a x n/a	107.0
3001-033	2810	4060	4410	4690 x 4070	135.0
3001-034	3270	4520	4870	4690 x 4070	157.0
3001-035	3730	4980	5330	4690 x 4070	164.0
3001-036	4200	5450	5800	4690 x 4070	172.0
3001-037	4660	5910	6260	4690 x 4070	177.0
3001-038	5130	6380	6730	4690 x 4070	185.0
3001-039	5590	6840	7190	5780 x 5160	199.0
3001-040	6050	7300	7650	5780 x 5160	228.0
3001-041	6520	7770	8120	5780 x 5160	232.0
3001-042	6980	8230	8580	5780 x 5160	244.0
3001-043	7450	8700	9050	5780 x 5160	248.0
3001-044	7910	9160	9510	5780 x 5160	256.0
3001-045	8370	9370	9970	5780 x 5160	261.0
3001-046	8840	9840	10440	5780 x 5160	269.0
3001-047	9300	10300	10900	5780 x 5160	276.0
3001-048	9770	10770	11370	5780 x 5160	306.0
3001-049	10230	11230	11830	5780 x 5160	310.0
3001-050	10690	11690	12290	5795 x 5170	327.0
3001-051	11160	12160	12760	5795 x 5170	334.0
3001-052	11520	12620	13120	5795 x 5170	343.0
3001-053	13290	13090	14890	5795 x 5170	347.0

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate.

² Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.