

## 3T Double Width Vertical Ladder 2.5 x 0.70m Scaffold Tower



[Representative image of product]

### Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 250kg
- Standard: BS EN 1004:2004
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: GB
- Recommended Usage: Intensive

### Common Dimensions

- Platform Length: 2500mm
- Platform Width: 1350mm
- Distance Between Rungs: 232mm

### Product Description

Ideal for use in industrial environments, this is a heavy-duty scaffold tower that is built using the 3T method or Through The Trap. Top-level quality components include locking castors, threaded levelling legs, locking brace hooks. Vertical Ladder design, with a built-in ladder section and rungs, spaced 232mm apart. Spare parts are available to replace damaged components or if you need to build additional platform heights. Manufactured in the UK, this range of scaffold towers is also available in double-width and a variety of platform sizes, from 2.0m, 2.5m and 3.0m lengths.

### Features

- Fully compliant using the 3T or Through The Trap build method
- 50mm scaffold tube construction with a heavy-duty spigot for maximum strength and crimped abuse-resistant joints
- Toe-board and guardrails for additional security
- Large trapdoor for easy access to top platform
- Quick assembly - designed for the professional user
- Rating - Platform 250kg / Structure 750kg
- Also available as a Single Width tower

## 3T Double Width Vertical Ladder 2.5 x 0.70m Scaffold Tower

### Product Dimensions

SKU	Platform Height <sup>2</sup> (mm)	Overall Height (mm)	Approx. Working Height <sup>1</sup> (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3001-054	1410	2660	3010	n/a x n/a	104.0
3001-055	1880	3130	3480	n/a x n/a	111.0
3001-056	2340	3590	3940	n/a x n/a	120.0
3001-057	2810	4060	4410	5190 x 4070	167.0
3001-058	3270	4520	4870	5190 x 4070	176.0
3001-059	3730	4980	5330	5190 x 4070	183.0
3001-060	4200	5450	5800	5190 x 4070	196.0
3001-061	4660	5910	6260	5190 x 4070	196.0
3001-062	5130	6380	6730	5190 x 4070	205.0
3001-063	5590	6840	7190	6280 x 5160	219.0
3001-064	6050	7300	7650	6280 x 5160	254.0
3001-065	6520	7770	8120	6280 x 5160	259.0
3001-066	6980	8230	8580	6280 x 5160	267.0
3001-067	7450	8700	9050	6280 x 5160	275.0
3001-068	7910	9160	9510	6280 x 5160	284.0
3001-069	8370	9370	9970	6280 x 5160	288.0
3001-070	8840	9840	10440	6280 x 5160	297.0
3001-071	9300	10300	10900	6280 x 5160	304.0
3001-072	9770	10770	11370	6280 x 5160	339.0
3001-073	10230	11230	11830	6280 x 5160	344.0
3001-074	10690	11690	12290	6295 x 5170	361.0
3001-075	11160	12160	12760	6295 x 5170	368.0
3001-076	11520	12620	13120	6295 x 5170	377.0
3001-077	12060	13090	13660	6295 x 5170	382.0

<sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate.

<sup>2</sup> Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.