



Speedy Tower



Common Dimensions

| | |
|----------------------------------|-----------|
| Aluminium stiles diameter (mm) | 50 |
| Distance between rungs (mm) | 250 |
| Wheels diameter (mm) | 125 |
| Base length w/o stabilisers (mm) | 1,750 |
| Base width w/o stabilisers (mm) | 830 |
| Hatch size (mm) | 540 x 570 |

Product Dimensions

| PRODUCT SKU | PLATFORM HEIGHT (M) | APPROX WORKING HEIGHT* (M) | OVERALL HEIGHT (M) | BASE LENGTH INC STABILISERS (M) | BASE WIDTH INC STABILISERS (M) | WEIGHT (NETT KG) |
|-------------|---------------------|----------------------------|--------------------|---------------------------------|--------------------------------|------------------|
| 3010-030 | 0.9 | 2.5 | 1.8 | | | 28.7 |
| 3010-031 | 1.7 | 3.3 | 2.8 | | | 17.0 |
| 3010-032 | 3.4 | 5.0 | 4.6 | 3.9 | 3.4 | 35.0 |
| 3010-033 | 5.2 | 6.8 | 6.3 | 3.9 | 3.4 | 14.3 |

* Working height is calculated as 1,600mm plus the height of the platform or last climbing tread, whichever is appropriate.



Technical Description

The Speedy Tower is tough, efficient and versatile thanks to its foldable base and spun-rung ‘Duraclimb’ technology. The Speedy tower provides a strong but lightweight option designed for regular use with no tools required - simply slot and lock into place. The folding base unit is easy to manoeuvre around on four lockable castors, or fold in half to fit through narrow doorways. The addition of guardrail and extension packs allow the system to be used on projects up to 7 metres.

- » Quick and easy erection – no tools required
- » Manufactured from 50mm ‘duraclimb’ tube for regular use
- » Flexible modular design to reach different heights
- » Four lockable castors
- » Anti-slip 1.78 x 0.78m platform
- » Stabilisers included above 3.5m platform heights

Notice:

Pack 1 is the base pack. Simply add additional packs to gain extra working height in the following order:
 Pack 1 + 2 gives an approximate working height of 3.4m
 Pack 1 + 2 + 3 gives an approximate working height of 5.1m
 Pack 1 + 2 + 3 + 4 gives an approximate working height of 6.8m

Standards & Classification

- » Max Load 200kg
- » EN1004

Warranty

- » 3 Year

Commodity Code

- » 76169990

Shipping Dimensions

| PRODUCT SKU | SHIPPING LENGTH (MM) | SHIPPING WIDTH (MM) | SHIPPING HEIGHT (MM) | SHIPPING VOLUME (M ³) | SHIPPING WEIGHT (GROSS KG) | BARCODE |
|-------------|----------------------|---------------------|----------------------|-----------------------------------|----------------------------|---------------|
| 3010-030 | 1,930 | 770 | 500 | 0,739 | 27.5 | 3178740036881 |
| 3010-031 | 1,800 | 770 | 800 | 0,110 | 10.7 | 3178740036898 |
| 3010-032 | 1,840 | 770 | 300 | 0,422 | 29 | 3178740036904 |
| 3010-033 | 1,840 | 770 | 250 | 0,352 | 20.6 | 3178740036911 |