

X Tower Mobile Scaffold Tower



Common Dimensions

Platform size (mm)	1,540 x 600
Wheels diameter (mm)	150
Adjustable sections (mm)	250

Product Dimensions

PRODUCT SKU	PLATFORM HEIGHT (M)	APPROX WORKING HEIGHT* (M)	OVERALL HEIGHT (M)	OVERALL WIDTH W/O STABILISERS (M)	OVERALL DEPTH STABILISERS (M)	FRAME WIDTH (M)	OVERALL WIDTH STABILISERS (M)	WEIGHT (NETT KG)
3010-035	2.0	3.6	3.1	0.84	2.1	1.7	2.4	68.0
3010-036	2.8	4.4	3.9	0.84	2.1	1.6	2.3	75.0
3010-037	Carry Trolley							

* Working height is calculated as 1,600mm plus the height of the platform or last climbing tread, whichever is appropriate.



Technical Description

The X-Tower is approved to EN1004 and can be erected in three minutes by one person with the minimum of training from the ground for maximum safety. The compact design can be stored and transported inside a small van and erected by one person in three minutes. Manufactured using industrial grade components for frequent use. Intuitive gravity latches make rung-by-rung height adjustment effortless allowing the tower to be quickly deployed to your desired height.

- » Telescopic design can be erected in less than 3 minutes by one person
- » Industrial strength design and components for frequent use
- » Effortless multi height adjustment up to a 2.8m platform (4.4m working) height
- » No loose components to lose or leave behind
- » Two components – tower and folding anti-slip platform
- » Compact enough to transport in a small van
- » Fitted with four independent adjustable-height locking castors
- » Foldable toe boards integrated to the platform
- » Stabilisers are millimetre adjustable for uneven ground
- » Folding guardrails

Standards & Classification

- » Max Load 150kg
- » EN1004

Warranty

- » 5 Year

Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (MM)	SHIPPING WIDTH (MM)	SHIPPING HEIGHT (MM)	SHIPPING VOLUME (M ³)	SHIPPING WEIGHT (GROSS KG)	BARCODE
3010-035	980	820	1.340	1.0768	68.0	3178740162009
3010-036	980	920	1.410	1.2713	75.0	3178740162016