

3T Single Width 232 Frame Access 2.0 X 0.70m Scaffold Tower



[Representative image of product]

Product Description

Ideal for use in industrial environments, this is a heavy-duty scaffold tower that is built using the 3T method or Through The Trap. Top-level quality components include locking castors, threaded levelling legs, locking brace hooks. Frame Access design, with rungs spaced 232mm apart, removes the need for a separate or built-in ladder frame. Spare parts are available to replace damaged components or if you need to build additional platform heights. Manufactured in the UK, this range of scaffold towers is also available in double-width and a variety of platform sizes, from 2.0m, 2.5m and 3.0m lengths.

Features

- Fully compliant using the 3T or Through The Trap build method
- 50mm scaffold tube construction with a heavy-duty spigot for maximum strength and crimped abuse-resistant joints
- Toe-board and guardrails for additional security
- Large trapdoor for easy access to top platform
- Quick assembly - designed for the professional user
- Rating - Platform 250kg / Structure 750kg
- Also available as a Double Width tower

Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 250kg
- Standard: BS EN 1004:2004
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: GB
- Recommended Usage: Intensive

Common Dimensions

- Platform Length: 2000mm
- Platform Width: 700mm
- Distance Between Rungs: 232mm

3T Single Width 232 Frame Access 2.0 X 0.70m Scaffold Tower

Product Dimensions

SKU	Platform Height ² (mm)	Overall Height (mm)	Approx. Working Height ¹ (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3012-000	1410	2660	3010	n/a x n/a	69.0
3012-001	1880	3130	3480	n/a x n/a	89.0
3012-002	2340	3590	3940	n/a x n/a	108.0
3012-003	2810	4060	4410	4690 x 3460	118.0
3012-004	3270	4530	4870	4690 x 3460	123.0
3012-005	3730	4980	5330	4690 x 3460	128.0
3012-006	4200	5450	5800	4690 x 3460	132.0
3012-007	4660	5910	6260	4690 x 3460	135.0
3012-008	5130	6380	6730	4690 x 3460	147.0
3012-009	5590	6840	7190	5780 x 4550	151.0
3012-010	6050	7300	7650	5780 x 4550	177.0
3012-011	6520	7770	8120	5780 x 4550	180.0
3012-012	6980	8230	8580	5780 x 4550	185.0
3012-013	7450	8700	9050	5780 x 4550	189.0
3012-014	7910	9160	9510	5780 x 4550	194.0

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate.

² Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.

Packaging Material: No Packaging