

Professional Single Section Ladder



[Representative image of product]

Product Description

For professional & trade use. Ideal if you are looking for a top-quality ladder to use around the home or business. This professional-grade ladder is manufactured to the latest EN131 Professional standards and includes a stabilising bar that requires fitting before first use. Once fitted, the ladder cannot be used without the stabiliser bar. These ladders are not only lightweight to carry, but made from super strong aluminium giving you a stable platform that feels safer from which to work. The ladder has thicker box section stiles than cheaper alternatives, which makes the ladder stiffer, less likely to twist and longer-lasting. It is supplied with an extended 3-year warranty so you can expect to get many years of service from our top quality ladders manufactured here in the UK.

Features

- Commercial strength box section construction with twist proof rung joints
- Reduce fatigue with deep, comfortable D-shaped rungs
- Slip-resistant high traction rungs
- Stabilising bar supplied with ladders over 3m - requires fitting before first use
- Anti-slip rubber feet

Specifications

- Brand: TB Davies
- Warranty: 3-year
- Max Load: 150kg
- Standard: EN131 Professional
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: GB
- Recommended Usage: Regular

Common Dimensions

- Rung Depth: 35mm
- Distance Between Rungs: 250mm

Availability & Delivery

Stock item. Delivery next day.

(See exceptions, if applicable, overleaf)

Professional Single Section Ladder

Product Dimensions

SKU	Rungs /Sections	Closed Length (mm)	Last Climbing Height	Approx. Working Height ¹ (mm)	Extended Length (mm)	Width (mm)	Depth (mm)	Nett Weight (kg)
1102-050	9 x 1	2500	1400	3000	2500	410	64	6.0
1102-051	11 x 1	3000	1900	3500	3000	410	64	7.0
1102-052	13 x 1	3500	2300	3900	3500	410	64	8.0
1102-053	15 x 1	4000	2800	4400	4000	410	64	9.0
1102-054	17 x 1	4500	3300	4900	4500	410	64	10.0
1102-055	19 x 1	5000	3800	5400	5000	410	64	11.0
1102-056	21 x 1	5500	4200	5800	5500	410	64	12.0

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1102-050	5060356919932	2500	410	64	0.066	7.4
1102-051	5060356919949	3000	410	64	0.079	8.4
1102-052	5060356919956	3500	410	64	0.092	10.8
1102-053	5060356919963	4000	410	64	0.105	11.8
1102-054	5060356919970	4500	410	64	0.118	13.5
1102-055	5060356919987	5000	410	64	0.131	14.5
1102-056	5060356919994	5500	410	64	0.144	15.5

Packaging Material: No Packaging