

# **HDUTY-P Aluminium Professional Platform Step**



[Representative image of product]

# **Specifications**

- Brand: TB Davies - Warranty: 5-year - Max Load: 150kg

- Standard: EN131 PROFESSIONAL

- Material: Aluminium - Commodity Code: 76169990 - Country of Origin: IT - Recommended Usage: Regular

## **Common Dimensions**

- Tread Depth: 85mm

- Distance Between Treads: 230mm

- Storage Depth: 140mm

- Top Platform Tread (LxW): 330 x 255mm

- Handrail Height: 610mm

# **Packaging Material**

- No Packaging

# **Availability & Delivery**

- Stock item. Delivery next day. (See exceptions, if applicable, overleaf)

# **Product Description**

Ideal for all professional and commercial use. The TB Davies Professional Platform Step Ladder replaces the classic class 1 step. Our new step ladder complies with current EN131 Professional standards, so you can be assured that you are standing on a top-quality ladder product. The TB Davies Professional Platform Step is a step ladder designed for hard work, day after day. The TB Davies Professional Platform step is manufactured using ribbed aluminium stiles, with a non-slip platform tread, a fitted top tool tray and an integrated hook. The hinges are die-cast and have polyamide/nylon fixings, making the step opening smoother and helping prevent wear and tear. The treads are 85mm deep, offering greater comfort on your feet. The treads are crimped, not riveted, for maximum strength. Our professional steps have one of the broadest size ranges, from 3 to 12 treads. Note, webbing straps fitted on all sizes from 5-treads and above.

## **Features**

- Aluminium die-cast platform for maximum grip
- Comfortable 85mm welded & crimped treads
- Heavy duty all aluminium construction for longlife
- Fitted with integrated tool tray and hook
- Oversized slip resistant feet provide extra firm footing

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

Date Created: November 20th, 2023



# **HDUTY-P Aluminium Professional Platform Step**

## **Product Dimensions**

SKU	Treads <sup>2</sup>	Platform Height (mm)	Approx. Working Height <sup>1</sup> (mm)	Closed Height (mm)	Open Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1202-023	3	650	2400	1340	1250	440	650	4.5
1202-024	4	885	2635	1565	1485	470	810	5.2
1202-025	5	1120	2870	1810	1720	500	970	6.8
1202-026	6	1355	3105	2055	1955	530	1130	7.5
1202-028	8	1825	3575	2545	2425	590	1480	9.5
1202-030	10	2275	4025	3035	2895	650	1840	12.0
1202-031	11	2520	4270	3280	3130	680	1990	13.2
1202-032	12	2760	4510	3525	3365	710	2150	14.2

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of ~75° degrees.

# **Shipping Dimensions**

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
1202-023	1380	440	115	0.07	4.5
1202-024	1620	470	115	0.088	5.2
1202-025	1880	500	115	0.108	6.8
1202-026	2120	530	115	0.129	7.5
1202-028	2620	590	115	0.178	9.5
1202-030	3120	650	140	0.284	12.0
1202-031	3370	680	140	0.321	13.2
1202-032	3620	710	140	0.36	14.2

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

<sup>&</sup>lt;sup>2</sup> Tread count includes the top platform step/top cap tool tray tread.