

# Maxi Platform Steps Ladders



[Representative image of product]

## Product Description

The Maxi platform step ladder is designed for intensive use and features a large cast aluminium safety platform set at a comfortable 75-degree angle. The large 110mm deep treads are secured using 'Duraclimb' spun-rung technology to provide the strongest possible mechanical connection for intensive use.

## Features

- Featuring tough spun-rung 'Duraclimb' technology for intensive use
- Comfortable 75 degree safe-climbing angle
- Large 110mm deep steps for fatigue-free standing
- High strength nylon components reduce wear and tear
- Spacious storage tray for material and tools

## Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 150kg
- Standard: EN131 Professional
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: IT
- Recommended Usage: Intensive

## Common Dimensions

- Tread Depth: 110mm
- Distance Between Treads: 250mm
- Storage Depth: 110mm
- Top Platform Tread (LxW): 265 x 265mm
- Handrail Height: 600mm

## Availability & Delivery

Stock item. Delivery next day.

(See exceptions, if applicable, overleaf)

# Maxi Platform Steps Ladders

## Product Dimensions

SKU	Treads <sup>2</sup>	Approx. Working Height <sup>1</sup> (mm)	Platform Height (mm)	Closed Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1211-023	3	2250	650	1380	440	700	4.2
1211-024	4	2480	880	1620	470	860	5.2
1211-025	5	2720	1120	1880	500	1020	6.2
1211-026	6	2960	1360	2120	530	1180	7.2
1211-027	7	3190	1590	2370	560	1340	8.2
1211-028	8	3420	1820	2620	590	1500	9.2

<sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

<sup>2</sup> Treads includes top platform step/top cap tool tray tread

## Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m <sup>3</sup> )	Gross Weight (kg)
1211-023	5060356913305	1380	440	110	0.067	4.2
1211-024	5060356913312	1620	470	110	0.084	5.2
1211-025	5060356913329	1880	500	110	0.103	6.2
1211-026	5060356913336	2120	530	110	0.124	7.2
1211-027	5060356913343	2370	560	110	0.146	8.2
1211-028	5060356913350	2620	590	110	0.17	9.2

**Packaging Material:** Polywrap