INSUL8-P Fibreglass Professional Platform Step



Specifications

- Brand: TB Davies
- Warranty: 3-year
- Max Load: 150kg
- Standard: EN131 PROFESSIONAL
- Material: GRP Fibreglass/Aluminium
- Commodity Code: 39269097
- Country of Origin: CN
- Recommended Usage: Regular

Common Dimensions

- Tread Depth: 80mm
- Distance Between Treads: 280mm
- Storage Depth: 153mm
- Top Platform Tread (LxW): 345 x 255mm
- Handrail Height: 607mm

Packaging Material

- Polythene Wrap & Cardboard Header Card

Availability & Delivery

- Stock item. Delivery next day. (See exceptions, if applicable, overleaf)

[Representative image of product]

tb davies

Product Description

Our Heavy-Duty Fibreglass step ladder range incorporates a multi-functional tool tray with non-conductive stiles, making them ideal for working around electricity. The combination of super-strong C-section fibreglass stiles and reinforced aluminium treads gives you a durable yet lightweight and easy to handle step that is perfect for the busy trades-person.

Features

- Non-conductive fibreglass stiles to 30,000 volts (EN61478), ideal for working around electricity
- Integrated multi-function tool tray
- Reinforced 320 x 248mm checker-plate platform (platform steps only)
- Comfortable 80mm treads
- Hinged metal locking stays, provide optimal stability
- Box section back legs with heavy-duty bracing
- Large feet angled to maximise ground contact and reduce slip

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.



INSUL8-P Fibreglass Professional Platform Step

Product Dimensions

SKU	Treads ²	Platform Height (mm)	Approx. Working Height ¹ (mm)	Closed Height (mm)	Open Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1236-004	4	1041	2791	1808	1648	537	994	8.8
1236-005	5	1303	3053	2088	1910	572	1174	10.2
1236-006	6	1564	3314	2368	2171	606	1354	11.4
1236-008	8	2087	3837	2928	2694	674	1715	14.0

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of $\sim 75^{\circ}$ degrees.

² Tread count includes the top platform step/top cap tool tray tread.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1236-004	1808	430	153	0.119	9.0
1236-005	2088	445	153	0.142	10.4
1236-006	2368	460	153	0.167	11.6
1236-008	2928	497	153	0.223	14.2

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.