

# King Kombo Industrial Fibreglass



## Specifications

- Brand: Little Giant Ladders
- Warranty: 1-year
- Max Load: 150kg
- Standard: EN131 Professional
- Material: GRP Fibreglass/Aluminium
- Commodity Code: 39269097
- Country of Origin: CN
- Recommended Usage: Intensive

## Common Dimensions

- Rung Depth: 80mm
- Distance Between Rungs: 300mm

## Availability & Delivery

Stock item. Delivery next day.

(See exceptions, if applicable, overleaf)

[Representative image of product]

## Product Description

Little Giant's King Kombo™ Industrial is the world's first and only 3-in-1 extension ladder, leaning ladder and stepladder combination, in one lightweight package. King Kombo™ was built for those who get stuff done! King Kombo™, with ultra-heavy-duty feet, seriously aggressive tread for elite traction and durability for harsh industrial environments. King Kombo™ also brings a tough corner, pole, and stud gripping V-bar for the extension ladder position. This heavy-duty grip conforms to inside and outside corners and even offers protection for damageable leaning surfaces like paint, drywall, and stucco and round poles. Speed, power, and safety prepare to be faster and safer than ever on the job! Fitted with the patent-pending Ground Cue™, an audible and tactile signal to let you know you when you have reached the bottom step of the ladder.

## Features

- Ultra-heavy-duty feet with aggressive tread for elite traction & fitted with Ground Cue™ on the bottom tread
- Tough corner, pole and stud gripping V-bar for the extension ladder position
- Heavy-duty grip conforms to inside and outside corners and even offers protection for damageable leaning surfaces such as paint, drywall and stucco
- Patent-pending non-conductive Hi-Viz green fibreglass makes the ladder more noticeable
- Wide-flared side offers superior side-tip stability
- Straight side allows operators to access tight work spaces between stud gaps, ceiling trusses and attic access ports
- This ladder brings speed, power and safety to any job with palm buttons for easy adjustment

## King Kombo Industrial Fibreglass

### Product Dimensions

SKU	Rungs /Sections	Last Climbing Height	Approx. Working Height <sup>1</sup> (mm)	Extended Length (mm)	Closed Length (mm)	Storage Width (mm)	Storage Depth (mm)	Nett Weight (kg)
1303-205	5 x 2	1500	3100	2600	1540	640	180	9.0
1303-206	6 x 2	1800	3400	3000	1840	640	180	9.9
1303-208	8 x 2	3000	4600	4200	2440	730	180	12.8

SKU	Max Step Height (mm)	Approx. Working Height <sup>1</sup> (mm)	Open Step Depth (mm)	Open Step Height (mm)
1303-205	900	2500	910	1500
1303-206	1200	2800	1120	1800
1303-208	1800	3400	1500	2400

<sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

### Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m <sup>3</sup> )	Gross Weight (kg)
1303-205	5060356912957	1570	650	200	0.204	11.0
1303-206	5060356912964	1860	650	200	0.242	12.2
1303-208	5060356912971	2470	750	200	0.371	15.3

**Packaging Material:** Heavy-duty Cardboard Box

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.