

## King Kombo Professional

---



*[Representative image of product]*

### Product Description

Little Giant's King Kombo Professional is the world's first and only 3-in-1 extension ladder, leaning ladder and stepladder combination, in one lightweight package. King Kombo was built for those who get stuff done! King Kombo, with ultra-heavy-duty feet, seriously aggressive tread for elite traction and durability for harsh industrial environments. This professional step conforms to inside and outside corners and even offers protection for damageable leaning surfaces like paint, drywall, and stucco and round poles. Speed, power, and safety prepare to be faster and safer than ever on the job!

### Features

- Ultra-heavy-duty feet with aggressive tread for elite traction
- Heavy-duty grip conforms to inside and outside corners and even offers protection for damageable leaning surfaces such as paint, drywall and stucco
- Wide-flared side offers superior side-tip stability
- Straight side allows operators to access tight work spaces between stud gaps, ceiling trusses and attic access ports
- This ladder brings speed, power and safety to any job with palm buttons for easy adjustment

### Specifications

- Brand: Little Giant Ladder Systems
- Warranty: 5-year
- Max Load: 150kg
- Standard: EN131 PROFESSIONAL
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: CN
- Recommended Usage: Intensive

### Common Dimensions

- Rung Depth: 80mm
- Distance Between Rungs: 300mm

### Packaging Material

- Cardboard Box

### Availability & Delivery

- Stock item. Delivery next day.
- (See exceptions, if applicable, overleaf)

# King Kombo Professional

## Product Dimensions

SKU	Rungs /Sections	Last Climbing Height	Approx. Working Height <sup>1</sup> (mm)	Extended Length (mm)	Closed Length (mm)	Storage Width (mm)	Storage Depth (mm)	Nett Weight (kg)
1303-215	5 + 4	1430	3380	2900	1550	620	180	8.6
1303-216	6 + 4	2010	3960	3020	1850	640	180	10.0
1303-218	8 + 6	3250	5200	4240	2460	710	180	14.5

SKU	Max. Step Height (mm)	Approx. Working Height <sup>1</sup> (mm)	Open Step Depth (mm)	Open Step Height (mm)
1303-215	860	2810	910	1500
1303-216	1140	3090	1120	1800
1303-218	1730	3680	1500	2400

Where applicable, Approx. Working Height<sup>1</sup> is an approximate calculation of 1,950mm (6'4") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of ~75° degrees.

## Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
1303-215	1575	635	178	0.178	10.4
1303-216	1880	635	178	0.212	12.2
1303-218	2464	686	178	0.301	17.7

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

**TB Davies (Cardiff) Ltd**, Lewis Road, Cardiff, CF24 5EB, GB. +44(0)29 2132 0000 [www.tbdavies.co.uk](http://www.tbdavies.co.uk) Registered in England No.534073, VAT Reg. No.GB134144207  
Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.

2023-10-04 14:52:58