

Revolution™ Multi-Purpose Ladders



[Representative image of product]

Product Description

For over 40 years the original Little Giant Ladder has set the standard for articulating ladders. Today there's a new revolution in lightweight ladder technology— the Revolution from Little Giant! The Revolution uses the latest military grade aluminium technology. Therefore, it is ultra-strong, without adding weight, remaining light, and portable. Adding even more stability to our safest ladder was not easy. However, the revolutionary Quad-Lock™ hinge system does just that. The Quad-Lock™ hinge locks into place with four pins for increased stability and overall safety. The Revolution features a redesigned Rock Lock™ system that makes adjusting your ladder quick and easy. Simply push the lock to release, adjust the ladder, and then tap to lock. It is simple, fast, and safe. Since it is adjustable, the Revolution can be used safely on stairs, ramps, curbs, docks, or other uneven surfaces. The wide flared legs, Rock Locks™, Quad-Lock™ hinge, and military grade materials combine to make it the strongest, safest ladder on the planet.

Features

- 20% lighter than any comparable industrial-rated ladder
- Easy-to-use Rock-Locks™ for quick adjustment
- Unmatched stability thanks to the Quad-Lock™ hinge and wide-flared legs
- Highest quality construction from aerospace grade aluminium
- Tip & Glide™ wheels for manoeuvrability

Specifications

- Brand: Little Giant Ladder Systems
- Warranty: Lifetime
- Max Load: 150kg
- Standard: EN131
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: CN
- Recommended Usage: Intensive

Common Dimensions

- Rung Depth: 35mm
- Distance Between Rungs: 285mm

Availability & Delivery

Stock item. Delivery next day.

(See exceptions, if applicable, overleaf)

Revolution™ Multi-Purpose Ladders

Product Dimensions

SKU	Rungs /Sections	Last Climbing Height	Approx. Working Height ¹ (mm)	Extended Length (mm)	Closed Length (mm)	Storage Width (mm)	Storage Depth (mm)	Nett Weight (kg)
1303-344	4 x 4	3028	4628	2500–4200	1300	593	230	14.4
1303-345	5 x 4	4129	5729	3100–5400	1600	660	230	18.9
1303-346	6 x 4	5230	6830	3600–6500	1900	730	230	23.4

SKU	Max Step Height (mm)	Approx. Working Height ¹ (mm)	Open Step Depth (mm)	Open Step Height (mm)
1303-344	1101	2701	1000–1500	1200–2100
1303-345	1652	3252	1100–1900	1500–2700
1303-346	2202	3802	1300–2300	1800–3200

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1303-344	5060169486348	1300	610	255	0.202	17.0
1303-345	5060169486355	1600	680	255	0.277	20.9
1303-346	5060169486362	1900	755	255	0.366	26.3

Packaging Material: Heavy-duty Cardboard Box

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.