

## Revolution™ Multi-Purpose Ladders



[Representative image of product]

### Product Description

For over 40 years the original Little Giant Ladder has set the standard for articulating ladders. Today there's a new revolution in lightweight ladder technology— the Revolution from Little Giant! The Revolution uses the latest military grade aluminium technology. Therefore, it is ultra-strong, without adding weight, remaining light, and portable. Adding even more stability to our safest ladder was not easy. However, the revolutionary Quad-Lock™ hinge system does just that. The Quad-Lock™ hinge locks into place with four pins for increased stability and overall safety. The Revolution features a redesigned Rock Lock™ system that makes adjusting your ladder quick and easy. Simply push the lock to release, adjust the ladder, and then tap to lock. It is simple, fast, and safe. Since it is adjustable, the Revolution can be used safely on stairs, ramps, curbs, docks, or other uneven surfaces. The wide flared legs, Rock Locks™, Quad-Lock™ hinge, and military grade materials combine to make it the strongest, safest ladder on the planet.

### Features

- 20% lighter than any comparable industrial-rated ladder
- Easy-to-use Rock-Locks™ for quick adjustment
- Unmatched stability thanks to the Quad-Lock™ hinge and wide-flared legs
- Highest quality construction from aerospace grade aluminium
- Tip & Glide™ wheels for manoeuvrability

### Specifications

- Brand: Little Giant Ladders
- Warranty: Lifetime
- Max Load: 150kg
- Standard: EN131
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: CN
- Recommended Usage: Intensive

### Common Dimensions

- Rung Depth: 35mm
- Distance Between Rungs: 285mm

### Availability & Delivery

Stock item. Delivery next day.

(See exceptions, if applicable, overleaf)

## Revolution™ Multi-Purpose Ladders

### Product Dimensions

| SKU      | Rungs /Sections | Last Climbing Height | Approx. Working Height <sup>1</sup> (mm) | Extended Length (mm) | Closed Length (mm) | Storage Width (mm) | Storage Depth (mm) | Nett Weight (kg) |
|----------|-----------------|----------------------|--|----------------------|--------------------|--------------------|--------------------|------------------|
| 1303-344 | 4 x 4           | 3028                 | 4628                                     | 2500-4200            | 1300               | 593                | 230                | 14.4             |
| 1303-345 | 5 x 4           | 4129                 | 5729                                     | 3100-5400            | 1600               | 660                | 230                | 18.9             |
| 1303-346 | 6 x 4           | 5230                 | 6830                                     | 3600-6500            | 1900               | 730                | 230                | 23.4             |

| SKU      | Max Step Height (mm) | Approx. Working Height <sup>1</sup> (mm) | Open Step Depth (mm) | Open Step Height (mm) |
|----------|----------------------|--|----------------------|-----------------------|
| 1303-344 | 1101                 | 2701                                     | 1000-1500            | 0-2100                |
| 1303-345 | 1652                 | 3252                                     | 1100-1900            | 1500-2700             |
| 1303-346 | 2202                 | 3802                                     | 1300-2300            | 1800-3200             |

<sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

### Shipping Dimensions

| SKU      | Barcode       | Shipping Length (mm) | Shipping Width (mm) | Shipping Depth (mm) | Shipping Volume (m <sup>3</sup> ) | Gross Weight (kg) |
|----------|---------------|----------------------|---------------------|---------------------|-----------------------------------|-------------------|
| 1303-344 | 5060169486348 | 1300                 | 610                 | 255                 | 0.202                             | 16.0              |
| 1303-345 | 5060169486355 | 1600                 | 680                 | 255                 | 0.277                             | 21.0              |
| 1303-346 | 5060169486362 | 1900                 | 755                 | 255                 | 0.366                             | 26.0              |

**Packaging Material:** Heavy-duty Cardboard Box

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.