

Xtreme Multi-Purpose Ladders



[Representative image of product]

Product Description

The Little Giant Xtreme® is the pinnacle of Little Giant's 40 years of engineering the strongest, safest, most versatile ladders in the world. The Xtreme combines the strength, safety, and versatility of the Little Giant Revolution with several ground-breaking features, including the Comfort Step™ platform, AirDeck® workstation, and integrated leg levellers that allow the operator to adjust to uneven ground in seconds. Each side of the Xtreme telescopes independently, giving you the option of several sizes of stepladders. You can also adjust one side to work on staircases or uneven surfaces or as a 90-degree stepladder. The Xtreme is built using the latest military grade aluminium technology. Therefore, it is ultra-strong, without adding weight, remaining light, and portable. The Quad-Lock hinge allows you to use the ladder as a stable, wide-based, multi-height extension ladder. Finally, the inner and outer ladder assemblies separate to form two trestles for a time-saving scaffolding system. The Little Giant Xtreme is the finest multi-use ladder system in the world.

Features

- Palm pressure hinges with Quad-Lock™ pins for easy setup and rock solid stability
- Wider rungs mean more stability and comfort when working on the ladder
- Integrated standing platform for added comfort and stability
- Rock-Locks™ – Adjust the height of your ladder with a simple click and hook
- Tip & Glide™ wheels for manoeuvrability
- Work safely on uneven terrain / hands free adjustment
- Supplied with AirDeck accessory

Specifications

- Brand: Little Giant Ladder Systems
- Warranty: Lifetime
- Max Load: 150kg
- Standard: BS EN 131-4:2007
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: CN
- Recommended Usage: Intensive

Common Dimensions

- Rung Depth: 35mm
- Distance Between Rungs: 285mm

Availability & Delivery

Stock item. Delivery next day.

(See exceptions, if applicable, overleaf)

Xtreme Multi-Purpose Ladders

Product Dimensions

SKU	Rungs /Sections	Last Climbing Height	Approx. Working Height ¹ (mm)	Extended Length (mm)	Closed Length (mm)	Storage Width (mm)	Storage Depth (mm)	Nett Weight (kg)
1303-600	4 x 4	3028	4628	2500–4200	1300	593	230	17.3
1303-601	5 x 4	4129	5729	3100–5400	1600	660	230	18.9
1303-602	6 x 4	5230	6830	3600–6500	1900	730	230	28.6

SKU	Max Step Height (mm)	Approx. Working Height ¹ (mm)	Open Step Depth (mm)	Open Step Height (mm)
1303-600	1101	2701	1000–1500	1200–2100
1303-601	1652	3252	1100–1900	1500–2700
1303-602	2202	3802	1300–2300	1800–3200

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1303-600	5060356911110	1350	710	240	0.23	21.9
1303-601	5060356911127	1650	710	240	0.281	26.5
1303-602	5060356911134	2000	800	240	0.384	32.0

Packaging Material: Heavy-duty Cardboard Box

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.