

Safety Cage Series 2.0



[Representative image of product]

Product Description

It's not a ladder, it's the Little Giant Safety Cage. With the Cage, you can access workspaces that would typically require tying-off, scaffolding or lifts, all with less time and labour than other climbing solutions. The Cage has a comfortable standing surface with a fully enclosed toe kick and wraparound enclosure, making it faster, safer and less expensive than many scaffolding or lift options. Plus, because you can work hands-free, the Safety Cage is perfect for jobs like maintaining large HVAC equipment or installing stage lighting.

Features

- Enclosed Safety Cage eliminates tie-off requirement
- Compliant with industry rules for three points of contact
- Ground Cue bottom rung alert lets you know when you've reached the bottom rung
- Tip & Glide wheels increase portability during transportation
- Wheel lift castors allow you to roll the ladder while fully deployed, and lock in place for secure climbing
- Light enough to work on weight-limited stages and upper floors
- Non-conductive fibreglass rails are ideal when working around electricity
- Hi-Viz green fibreglass increases the Cage's visibility, preventing accidental bumping

Specifications

- Brand: Little Giant Ladder Systems
- Warranty: 1-year
- Max Load: 150kg
- Standard: EN131-7:2013
- Material: Fibreglass
- Commodity Code: 39269097
- Country of Origin: CN
- Recommended Usage: Intensive

Common Dimensions

- Tread Depth: 76mm
- Distance Between Treads: 300mm
- Storage Depth: 150mm
- Top Platform Tread (LxW): 460 x 530mm
- Handrail Height: 1070mm

Packaging Material

- Cardboard/Polywrap

Availability & Delivery

- Stock item. Bulky delivery up to 7 days.
(See exceptions, if applicable, overleaf)

Safety Cage Series 2.0

Product Dimensions

SKU	Treads ²	Platform Height (mm)	Approx. Working Height ¹ (mm)	Closed Height (mm)	Open Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1304-092	2	560	2510	1960	1653	830	860	23.3†
1304-094	4	1180	3130	2540	2220	900	1210	27.0†
1304-096	6	1700	3650	3150	2787	980	1560	31.8†
1304-098	8	2260	4210	3760	3352	1050	1910	35.1†
1304-100	10	2840	4790	4360	3921	1120	2260	42.8†

Where applicable, Approx. Working Height¹ is an approximate calculation of 1,950mm (6'4") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of ~75° degrees.

† Heavy Item – 2-person lift required.

² Tread count includes the top platform step/top cap tool tray tread.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1304-092	2050	880	210	0.379	27.7†
1304-094	2630	910	210	0.503	33.4†
1304-096	3200	1000	210	0.672	39.2†
1304-098	3800	1070	210	0.854	43.9†
1304-100	4360	1100	210	1.007	52.5†

† Heavy Item – 2-person lift required.

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

TB Davies (Cardiff) Ltd, Lewis Road, Cardiff, CF24 5EB, GB. +44(0)29 2132 0000 www.tbdavies.co.uk Registered in England No.534073, VAT Reg. No.GB134144207
Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.

2025-07-02 15:19:13