

## EuroFold Loft Ladder



[Representative image of product]

### Product Description

Easy to open and quick to close, the EuroFold is a superior quality loft ladder that helps you get more from your living space. Putting away suitcases or storing your Christmas decorations has never been easier. The EuroFold loft ladder fits between standard UK roof joists making installation quick and straightforward. A continuous seal wraps around the entire frame to give maximum protection from cold drafts blowing from the loft into your warm home. The seal and extra-thick wooden frame construction, together with 33mm thick trapdoor help achieve a tested U-value of 1.11 W / m<sup>2</sup>K. The incredibly strong frame is manufactured from 18mm engineered timber, to improve the insulation properties and stiffen the frame for a secure fit. All the components necessary for installation, including the fixings and screws, are included for quick and easy assembly. The kit is completed with a loft pole to enable easy opening suitable for ceilings up to 2.8m. Precision manufactured in Europe's Clean Tech Valley using renewable energy and PEFC sustainably sourced timber. Ladder section dimensions: 990 x 400 x 240mm. When fitting the ladder sections into position, the 3 x sections will sit securely on brackets 100mm off the loft hatch door. The overall height of the ladder sections will become 340mm.

Timber materials used are certified PEFC and from sustainably managed forests, recycled and controlled sources [PEFC 16-37-2313].

### Features

- Tested U-Value of 1.11W/m<sup>2</sup>K for improved insulation and reduced heat loss
- Fits between standard UK loft joists
- Requires no headroom or storage space in the loft
- Some assembly required before installation
- 33mm thick insulated white trapdoor and 18mm thick frame, together with continuous seal keeps cool drafts out
- Spring counter balancing system for easy operation
- Slip-resistant mortice and tenon secured treads

### Specifications

- Brand: TB Davies
- Warranty: 1-year
- Max Load: 150kg
- Standard: EN14975
- Material: Timber
- Commodity Code: 44189990
- Country of Origin: AT
- Recommended Usage: Regular

### Frame Dimensions

- Distance Between Treads: 235mm
- Tread Width: 345mm
- Tread Depth: 80mm
- Tested U-Value: **1.11W/m<sup>2</sup>K**
- Insulated Hatch Thickness: 33mm
- Frame/Stile/Tread: Plywood/Nordic Spruce/Nordic Spruce

### Availability & Delivery

Stock item. Delivery next day.

## EuroFold Loft Ladder

### Product Dimensions

SKU	Treads /Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance Length (mm)	Going (mm)
1530-000	4 x 3	1200 x 550	1190 x 540	2800	550	1200

### Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m <sup>3</sup> )	Gross Weight (kg)
1530-000	5060169480964	1250	650	400	0.325	27.0

### Optional Extras / Spare Parts

SKU	Description
1530-002A	EuroFold Replacement Spares Bag
1530-001	TB Davies Loft Ladder Additional Handrail
1530-004H	Loft Ladder Replacement Feet X 2

**Packaging Material:** Cardboard Box



Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.  
This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.