

TB Davies ENVIROFOLD Wooden Loft Ladder



[Representative image of product]

Specifications

- Brand: TB Davies - Warranty: 1-year - Max Load: 150kg - Standard: EN14975 - Material: Timber

- Commodity Code: 44189990 - Country of Origin: AT - Recommended Usage: Regular

Frame Dimensions

- Distance Between Treads: 235mm

- Tread Width: 345mm - Tread Depth: 80mm

- Tested U-Value: 1.11W/m2K - Insulated Hatch Thickness: 33mm

- Frame/Stile/Tread: Plywood/Nordic Spruce/Nordic Spruce

Packaging Material

- Cardboard Box

Availability & Delivery

- Stock item. Delivery next day.

Product Description

The EnviroFold is the contractor's choice of loft ladder being both quick to install and a snug fit between standard UK joists. The thickly insulated trapdoor is finished in white and sprung counterbalanced for smooth operation. Suitable for ceiling heights up to 2.8m the innovative design takes up no space in the attic. A continuous air seal, and extra-thick wooden frame combine with a 33mm thick trapdoor to achieve a tested U-value of 1.11 W/m²K. The deep anti-slip treads are morticed into the stiles using traditional methods for maximum comfort. This quick installation kit comes complete with angled feet, a handrail for added security and an operating pole and hook. Precision manufactured in Europe?s Clean Tech Valley using renewable energy and PEFC sustainably sourced timber. Ladder section dimensions: 990 x 400 x 240mm. When fitting the ladder sections into position, the 3 x sections will sit securely on brackets 100mm off the loft hatch door. The overall height of the ladder sections will become 340mm.

Timber materials used are certified PEFC and from sustainably managed forests, recycled and controlled sources [PEFC 16-37-2313].

Features

- Tested U-Value of 1.11W/m2K for improved insulation and reduced heat loss
- Supplied with slip-resistant feet and handrail for extra security
- 33mm deep insulated white trapdoor with push/pull lock
- 18mm thick frame features continuous seal that keeps cool drafts out
- Slip-resistant mortice and tenon secured treads, only final assembly required for quick installation
- Requires no headroom or storage space in the loft
- Manufactured using PEFC sustainably sourced timber
- Manufactured using 100% renewable energy



Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

Date Created: November 20th, 2023



TB Davies ENVIROFOLD Wooden Loft Ladder

Product Dimensions

SKU	Treads /Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance Length (mm)	Going (mm)	Nett Weight (kg)
1530-005	4 x 3	1200 x 550	1190 x 540	2800	550	1200	26.5†

[†] Heavy Item – 2-person lift required.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
1530-005	1250	650	400	0.325	27.5†

[†] Heavy Item - 2-person lift required.

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.