

## STEPMOBILE+ Steel Trade Mobile Step



### **Specifications**

- Brand: TB Davies - Warranty: 1-year - Max Load: 150kg - Standard: EN131-7:2013

- Material: Steel

- Commodity Code: 7326903000 - Country of Origin: GB - Recommended Usage: Intensive

#### **Common Dimensions**

- Rung Depth: 406mm

- Distance Between Rungs: 210mm

- Handrail Height: 952mm

#### **Packaging Material**

- Polywrap

#### **Availability & Delivery**

- Non-stock item. Delivery up to 28 days. (See exceptions, if applicable, overleaf)

[Representative image of product]

#### **Product Description**

Manufactured to the demanding requirements of British Standards EN131-7 with a flared base for maximum stability. Strong sprung castors lock and hold in place when weight is applied with long double handrails and a guard railed top tread provide extra assurance for users.

\*\*Not suitable for outdoor use\*\*

#### **Features**

- Flared base for added stability
- Spring loaded swivel castors retract when weight is applied
- Dome covers have high grip rubber wrap-around bumpers
- Large 180mm ribbed rubber covered treads
- Large 406 x 406mm platform
- Continuous hand and guardrail for safety
- Robust tubular steel construction
- Hard wearing powder coated finish in a choice of colour

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

Date Created: November 20th, 2023



# **STEPMOBILE+ Steel Trade Mobile Step**

#### **Product Dimensions**

SKU	Treads	Platform Height	Approx. Working Height <sup>1</sup> (mm)	Height (mm)	Width (mm)	Depth (mm)	Nett Weight (kg)
2010-062	2	508	2258	1460	615	730	14.0
2010-063	3	762	2512	1715	800	915	16.0
2010-064	4	1016	2766	1965	1000	1075	19.0
2010-065	5	1270	3020	2220	1200	1240	22.0

Where applicable, Approx. Working Height1 is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of ~75° degrees.

#### **Shipping Dimensions**

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
2010-062	1460	615	730	0.655	14.0
2010-063	1715	800	915	1.255	16.0
2010-064	1965	1000	1075	2.112	19.0
2010-065	2220	1200	1240	3.303	22.0

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

<sup>†</sup> Heavy Item – 2-person lift required.

<sup>&</sup>lt;sup>2</sup> Tread count includes the top platform step/top cap tool tray tread.