

Mobile Safety Step (Punched)



Specifications

Brand: TB DaviesWarranty: 1-yearMax Load: 150kgStandard: EN131-7:2013

- Material: Steel

Commodity Code: 7326903000Country of Origin: GBRecommended Usage: Intensive

Common Dimensions

- Rung Depth: 180mm

- Distance Between Rungs: 210mm

- Handrail Height: 950mm

Availability & Delivery

Non-stock item. Delivery Up To 21 Days. (See exceptions, if applicable, overleaf)

[Representative image of product]

Product Description

Kitemarked and tested by BSI to EN131-7, these steps are constructed from strong tubular mild steel with double handrail, toe-boarded platform and enclosed guardrail for assured working and stock picking in commercial environments. Available in a range of sizes with an all-metal punched tread for maximum grip.

Features

- Large 560 x 400mm top platform tread to comfortably work from
- Locking device and anti-ascent bar
- Please note 10 tread & above supplied in 2 parts
- Easy one user manoeuvrability on 4 x rolling wheels
- Optional extras available for full customisation
- Not suitable for outdoor use
- Max load 150kg

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.



Mobile Safety Step (Punched)

Product Dimensions

SKU	Treads	Platform Height	Approx. Working Height ¹ (mm)	Height (mm)	Width (mm)	Depth (mm)	Nett Weight (kg)
2017-004	4	1000	2600	2000	905	965	32.0
2017-005	5	1250	2850	2250	950	1120	55.0
2017-006	6	1500	3100	2500	995	1275	62.0
2017-007	7	1750	3350	2750	1040	1430	70.0
2017-008	8	2000	3600	3000	1085	1585	78.0
2017-009	9	2250	3850	3250	1130	1740	90.0
2017-010	10	2500	4100	3500	1175	1895	98.0
2017-011	11	2750	4350	3750	1220	2050	106.0
2017-012	12	3000	4600	4000	1265	2205	116.0
2017-013	13	3250	4850	4250	1310	2360	122.0
2017-014	14	3500	5100	4500	1355	2515	130.0
2017-015	15	3750	5350	4750	1400	2670	138.0

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
2017-004	2000	965	905	1.747	32.00
2017-005	2250	1120	950	2.394	55.00
2017-006	2500	1275	995	3.172	62.00
2017-007	2750	1430	1040	4.09	70.00
2017-008	3000	1585	1085	5.159	78.00
2017-009	3250	1740	1130	6.39	90.00
2017-010	3500	1895	1175	7.793	98.00
2017-011	3750	2050	1220	9.379	106.00
2017-012	4000	2205	1265	11.157	116.00
2017-013	4250	2360	1310	13.139	122.00
2017-014	4500	2515	1355	15.335	130.00
2017-015	4750	2670	1400	17.756	138.00

Packaging Material — Polywrap

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.