X-TOWER Aluminium Industrial Telescopic Tower



Specifications

- Brand: TB Davies
- Warranty: 3-year
- Max Load: 150kg
- Standard: EN1004
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: FR
- Recommended Usage: Intensive

Common Dimensions

- Platform Length: 1540mm
- Platform Width: 600mm
- Distance Between Rungs: 250mm

Packaging Material

- Heavy-duty Cardboard Sleeve, Poly Wrap And Foam Inserts

Availability & Delivery

- Non-stock item. Delivery up to 28 days. (See exceptions, if applicable, overleaf)

[Representative image of product]

tb davies

Product Description

The X-Tower can be erected in three minutes by one person with the minimum of training from the ground for maximum safety. The compact design can be stored and transported inside a small van and erected by one person in three minutes. Manufactured using industrial grade components for frequent use. Intuitive gravity latches make rung-by-rung height adjustment effortless allowing the tower to be quickly deployed to your desired height. Compact closed dimensions of 1.34m opens up to 3.1m x 2.0m platform.

Features

- Revolutionary Telescopic design can be erected in less than 3 minutes by one person
- Industrial strength design and components for frequent use
- Effortless multi-height adjustment up to a 2.8m platform height
- Two components only, tower frame and folding, anti-slip platform with integrated toe-boards
- Compacts down to fit inside a small trade van
- 4 x Locking heavy-duty castors
- Stabiliser supports are millimetre adjustable for precise levelling
- No loose components to forget or leave behind

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.



X-TOWER Aluminium Industrial Telescopic Tower

Product Dimensions

SKU	Platform Height ² (mm)	Approx. Working Height ¹ (mm)	Overall Height (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3010-035	2000	3750	3100	2440 x 2050	62.0†
3010-036	2800	4550	3850	2340 x 2050	72.0†

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of $\sim 75^{\circ}$ degrees.

[†] Heavy Item – 2-person lift required.

 2 Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
3010-035	1340	980	820	1.077	68.0†
3010-036	1410	980	920	1.271	75.0†

† Heavy Item - 2-person lift required.

Optional Extras / Spare Parts

SKU	Description
3010-037	X-Tower Carriage Trolley

Availability & Delivery Exceptions³

SKU	Product Name	Delivery	
3010-035	2.0m TB Davies X-TOWER Aluminium Industrial Telescopic Tower	Non-stock item. Delivery up to 28 days.	
3010-036 2.8m TB Davies X-TOWER Aluminium Industrial Telescopic Tower		Non-stock item. Delivery up to 28 days.	

³ Delivery times quoted are working days, these can vary. For precise times, please contact our sales team.

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.