

Speedy 4 + 3T Frame Access Scaffold Tower Kits



[Representative image of product]

Product Description

Speedy 4 + 3T Aluminium Scaffold Tower is a revised design for the all-new EN1004:2020 standard. It is still the same rugged, efficient, and versatile thanks to its foldable base and spun-rung 'Duraclimb' technology. The Speedy Tower provides a solid but lightweight option designed for regular use with no tools required - slot and lock into place. The folding base unit is easy to manoeuvre around on four lockable castors or fold in half to fit through narrow doorways. It is removable to enable precise levelling adjustments. Use on even or uneven ground indoors or out. Kit-1 contains the parts necessary to allow the scaffold tower to reach a 1.6m high platform height. Kit-2 increases the platform height to 3.35m, and Kit-3 increases the platform height to 5.10m. Available in 3 x optional kit packs, complete with a protective guardrail for projects up to 7.1m working height. Please contact our sales team for full details of our training courses on correctly assembling 3T scaffold towers.

Features

- Available in 3 x optional platform height kits
- Manufactured from 40mm 'Duraclimb' tube with 250mm rung spacing
- Flexible modular design to reach different heights Quick and easy build – no tools required
- Anti-slip 1.48 x 0.58m platform & 150mm toe boards
- Stabilisers included in pack

Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 200kg
- Standard: EN1004:2020
- Material: Aluminium
- Commodity Code: 7616999099
- Country of Origin: FR
- Recommended Usage: Regular

Common Dimensions

- Platform Length: 1480mm
- Platform Width: 580mm
- Distance Between Rungs: 250mm

Availability & Delivery

Stock item. Delivery next day.

(See exceptions, if applicable, overleaf)

Speedy 4 + 3T Frame Access Scaffold Tower Kits

Product Dimensions

SKU	Platform Height ² (mm)	Overall Height (mm)	Approx. Working Height ¹ (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3010-114	1600	2750	3200	3100 x 3300	110.4
3010-115	3350	4750	4950	3600 x 4200	84.9
3010-116	5100	6750	6700	3600 x 4200	99.2

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate.

² Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
3010-114	1900	770	1300	1.902	110.40
3010-115	1800	770	1600	2.218	84.90
3010-116	1800	770	1850	2.564	99.20

Packaging Material — Cardboard/Paper/Headercard/Polywrap

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

TB Davies (Cardiff) Ltd, Lewis Road, Cardiff, CF24 5EB, GB. +44(0)29 2132 0000 www.tbdavies.co.uk Registered in England No.534073, VAT Reg. No.GB134144207
Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.

[2022-06-15 08:52:06]