

AGR Aluminium Industrial Scaffold Tower - Single Width



[Representative image of product]

Product Description

The TAMPER-PROOF Advanced Guardrail Tower is another solution to safe tower assembly. The Tamper Proof Advanced Guardrails cannot be removed without descending and removing the platform first. The ergonomic design lends itself to quick, easy assembly. It provides collective fall protection before the operator accesses the platform and cannot be removed before the operative descends from the platform. The specially designed guardrail units can be used in conjunction with our standard Single and Double Width Towers. Ideal for use in industrial environments, this is a heavy-duty scaffold tower. Top-level quality components include locking castors, threaded levelling legs, locking brace hooks. Frame Access design, with rungs spaced 232mm apart removes the need for a separate or built-in ladder frame. Spare parts are available to replace damaged components or if you need to build additional platform heights. Manufactured in the UK, this range of scaffold towers is also available in double-width and a variety of platform sizes, from 2.0m, 2.5m and 3.0m lengths.

Features

- Fewer components than braced towers reducing losses on-site and speeds up assembly/disassembly
- AGR provides collective protection as guardrail is in place before the user climbs the structure
- Correct Guardrail heights achieved every time
- 50mm scaffold tube construction with a heavy-duty spigot for maximum strength and Crimped abuse-resistant joints
- Toe-board and guardrails for additional security
- AGR frames make this a fast-assembly tower
- Rating - Platform 250kg / Structure 750kg
- Also available as a Double Width tower

Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 250kg
- Standard: BS EN 1004:2004
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: UK
- Recommended Usage: Intensive

Common Dimensions

- Platform Length: 2000mm
- Platform Width: 700mm
- Distance Between Rungs: 232mm

Availability & Delivery

- Non-stock item. Delivery up to 14 days.
(See exceptions, if applicable, overleaf)

AGR Aluminium Industrial Scaffold Tower - Single Width

Product Dimensions

SKU	Platform Height ² (mm)	Approx. Working Height ¹ (mm)	Overall Height (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3012-052	2340	4090	3590	n/a x n/a	106.0†
3012-053	2810	4560	4060	4690 x 3460	135.0†
3012-054	3270	5020	4530	4690 x 3460	142.0†
3012-055	3730	5480	4980	4690 x 3460	148.0†
3012-056	4200	5950	5450	4690 x 3460	151.0†
3012-057	4660	6410	5910	4690 x 3460	167.0†
3012-058	5130	6880	6380	4690 x 3460	194.0†
3012-059	5590	7340	6840	5780 x 4550	200.0†
3012-060	6050	7800	7300	5780 x 4550	204.0†
3012-061	6520	8270	7770	5780 x 4550	214.0†

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of ~75° degrees.

² Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

TB Davies (Cardiff) Ltd, Lewis Road, Cardiff, CF24 5EB, GB. +44(0)29 2132 0000 www.tbdavies.co.uk Registered in England No.534073, VAT Reg. No.GB134144207 Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.

2024-07-16 09:41:09