

## AGR Aluminium Industrial Scaffold Tower - Double Width

**IMAGE  
UNAVAILABLE**

WWW.TBDAVIES.CO.UK

### Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 250kg
- Standard: BS EN 1004:2004
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: UK
- Recommended Usage: Intensive

### Common Dimensions

- Platform Length: 2000mm
- Platform Width: 1350mm
- Distance Between Rungs: 0mm

### Availability & Delivery

- Product no longer available  
(See exceptions, if applicable, overleaf)

[Representative image of product]

### Product Description

The TAMPER-PROOF Advanced Guardrail Tower is another solution to safe tower assembly. The Tamper Proof Advanced Guardrails cannot be removed without descending and removing the platform first. The ergonomic design lends itself to quick, easy assembly. It provides collective fall protection before the operator accesses the platform and cannot be removed before the operative descends from the platform. The specially designed guardrail units can be used in conjunction with our standard Single and Double Width Towers. Ideal for use in industrial environments, this is a heavy-duty scaffold tower. Top-level quality components include locking castors, threaded levelling legs, locking brace hooks. Frame Access design, with rungs spaced 232mm apart, removes the need for a separate or built-in ladder frame. Spare parts are available to replace damaged components or if you need to build additional platform heights. Manufactured in the UK, this range of scaffold towers is also available in double-width and a variety of platform sizes, from 2.0m, 2.5m and 3.0m lengths.

### Features

- Fewer components than braced towers reducing losses on-site and speeds up assembly/disassembly
- AGR provides collective protection as guardrail is in place before the user climbs the structure
- Correct Guardrail heights achieved every time
- 50mm scaffold tube construction with a heavy-duty spigot for maximum strength and Crimped abuse-resistant joints
- Toe-board and guardrails for additional security
- AGR frames make this a fast-assembly tower
- Rating - Platform 250kg / Structure 750kg
- Also available as a Single Width tower

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.  
This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

**TB Davies (Cardiff) Ltd**, Lewis Road, Cardiff, CF24 5EB, GB. +44(0)29 2132 0000 [www.tbdavies.co.uk](http://www.tbdavies.co.uk) Registered in England No.534073, VAT Reg. No.GB134144207  
Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.

2024-07-16 09:41:19

# AGR Aluminium Industrial Scaffold Tower - Double Width

## Product Dimensions

| SKU      | Platform Height <sup>2</sup> (mm) | Approx. Working Height <sup>1</sup> (mm) | Overall Height (mm) | Stabiliser Length x Width (mm) | Nett Weight (kg) |
|----------|-----------------------------------|------------------------------------------|---------------------|--------------------------------|------------------|
| 3015-052 | 2340                              | 4090                                     | 3590                | n/a x n/a                      | 114.0†           |
| 3015-053 | 2810                              | 4560                                     | 4060                | 4690 x 4070                    | 176.0†           |
| 3015-054 | 3270                              | 5020                                     | 4520                | 4690 x 4070                    | 184.0†           |
| 3015-055 | 3730                              | 5480                                     | 4980                | 4690 x 4070                    | 191.0†           |
| 3015-056 | 4200                              | 5950                                     | 5450                | 4690 x 4070                    | 195.0†           |
| 3015-057 | 4660                              | 6410                                     | 5910                | 4690 x 4070                    | 215.0†           |
| 3015-058 | 5130                              | 6880                                     | 6380                | 4690 x 4070                    | 250.0†           |
| 3015-059 | 5590                              | 7340                                     | 6840                | 5780 x 5160                    | 263.0†           |
| 3015-060 | 6050                              | 7800                                     | 7300                | 5780 x 5160                    | 268.0†           |
| 3015-061 | 6520                              | 8270                                     | 7770                | 5780 x 5160                    | 287.0†           |

Where applicable, Approx. Working Height<sup>1</sup> is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

Ladders set at an angle of ~75° degrees.

† Heavy Item – 2-person lift required.

<sup>2</sup> Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.  
This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.