

EUROFOLD LOFT



ENVIROFOLD LOFT



FIREFOLD LOFT



LUXFOLD LOFT



MINIFOLD LOFT



ELECTRIC LOFT



Tested to U-Value (Lower Is better)	1.11W/m2K	1.11W/m2K	0.667W/m2K	0.59W/m2K	1.11W/m2K	1.3W/m2K
Hatch Thickness	33mm	33mm	60mm	87mm	33mm	65mm
Material - Frame	Plywood	Plywood	Spruce	Spruce	MDF	Metal + MDF
Material - Stile	Nordic Spruce	Nordic Spruce	Nordic Spruce	Nordic Spruce	Metal	Metal
Material - Tread	Nordic Spruce	Nordic Spruce	Nordic Spruce	Nordic Spruce	Metal	Metal
Handrail	-	Yes (x1)	Yes (x1)	Yes (x1)	-	-
Assembly	Some Assembly Required	Some Assembly Required	Some Assembly Required	Fully Assembled	Assembly Required	Assembly Required
Lock Mechanism	Simple	Simple	Simple	2-Part Metal Lock System	-	-
Tread Joint	Dove-Tailed	Dove-Tailed	Dove-Tailed	Dove-Tailed	-	-
Loft Ladder Pole	Yes	Yes	Yes	Yes	Yes	Yes
Operation	Manual	Manual	Manual	Manual	Manual	Electric (Remote)
Fire Rated (EN1634) 30-minutes	-	-	Yes	-	-	-
Safety Standard	EN14975	EN14975	EN14975	EN14975	EN14975	EN14975