



LOFT LADDERS



*Product Web Page





Tested to U-Value:

0.59w/m²k

(Lower is Better)

Hatch Thickness:

87mm

Materials:

Spruce Frame

Nordic Spruce Stringer

White HDF Hatch

Handrail:

Yes (x1)

Assembly:

Fully Assembled

Lock Mechanism:

2-part metal lock system

Tread Joint:

Dove-tailed

Feet on Ladder:

Yes

Loft Ladder Pole:

Yes (Metal)

Tested to U-Value:

1.11w/m²k

(Lower is Better)

Hatch Thickness:

33mm

Materials:

MDF Frame

Nordic Spruce Stringer

White HDF Hatch

Handrail:

Yes (x1)

Assembly:

Some Assembly Required

Lock Mechanism:

Simple

Tread Joint:

Dove-tailed

Feet on Ladder:

Yes

Loft Ladder Pole:

Yes (Timber)

Tested to U-Value:

1.11w/m²k

(Lower is Better)

Hatch Thickness:

33mm

Materials:

MDF Frame

Nordic Spruce Stringer

White HDF Hatch

Handrail:

N/A

Assembly:

Assembly Required

Lock Mechanism:

Simple

Tread Joint:

Dove-tailed

Feet on Ladder:

No

Loft Ladder Pole:

Yes (Timber)

| SKU | TREADS/SECTIONS | APERTURE L X W (MM) | MAX. FLOOR TO CEILING (MM) | GOING (MM) |
|------------------------|-----------------|---------------------|----------------------------|------------|
| 1530-010 LUXFOLD | 4 X 3 | 1200 X 700 | 2800 | 1300 |
| 1530-005 ENVIROFOLD | 4 X 3 | 1200 X 600 | 2800 | 1300 |
| 1530-000 EUROFOLD | 4 X 3 | 1200 X 600 | 2800 | 1300 |