

**tb davies**

## DESIGNED FOR SAFETY

TB DAVIES FIREFOLD  
LOFT LADDER FROM

**£572** RRP +VAT

✓ 30-MINUTE FIRE RATED

✓ PEFC RATED LOFT LADDERS



Visit [tbdavies.co.uk](http://tbdavies.co.uk)



**PEFC™**  
PEFC/16-37-2313

Promoting Sustainable  
Forest Management  
[www.pefc.co.uk](http://www.pefc.co.uk)



WATCH THE  
INSTALLATION VIDEO

**0.67 W / M<sup>2</sup>K**  
LOWER SCORE IS BETTER

COMPLETE LOFT LADDER FRAME AND  
3-SECTION FOLDING LADDER ALL MOUNTED  
ON A 33MM DEEP INSULATED HATCH  
WITH CONTINUOUS SEAL TO PREVENT  
DRAUGHTS.



DESIGNED TO  
WITHSTAND FIRE  
FOR UP TO 30  
MINUTES

(EL230) FIRE RATING

FOR DWELLINGS  
REQUIRING A FIRE  
RATED LOFT LADDER

60MM DEEP INSULATED HATCH  
TESTED TO A U-VALUE OF 0.59  
W / M<sup>2</sup>K

SLIP RESISTANT DOVETAIL TREADS

COMES COMPLETE WITH  
SAFETY HANDRAIL AND TWIN  
SLIP ON FEET.



PEFC SUSTAINABLY SOURCED  
TIMBER

**1-YEAR WARRANTY • 150 KG WORK LOAD • PROFESSIONAL USE**

SKU	TREADS X SECTIONS	APERTURE L X W (MM)	FRAME SIZE L X W (MM)	MAX. FLOOR TO CEILING (MM)	MAX. SWING CLEARANCE (MM)	GOING (MM)	WEIGHT (KG)
1530-040	4 x 3	1200 x 600	1190 x 590	2750	550	1200	27.5

Created: October, 2022